US EPA RECORDS CENTER REGION 5



942641

4/25/91

SCREENING SITE INSPECTION REPORT
FOR
T. O. PLASTICS

CLEARWATER, MINNESOTA
U.S. EPA ID: MNDO06171847
SS ID: NONE

TDD: F05-8811-003 PAN: FMN0188SA

APRIL 25, 1991



ecology and environment, inc.

111 WEST JACKSON BLVD., CHICAGO, ILLINOIS 60604, TEL. 312-663-9415 International Specialists in the Environment recycled paper



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 5

230 SOUTH DEARBORN ST. CHICAGO, ILLINOIS 60604

SHR-11-SSI

Ron Swenson, Supervisor
Site Response Section
Minnesota Pollution Control Agency
520 Lafayette Road
St. Paul, Minnesota 55155

Site Name: T.O. PLASTICS

Location: CLEARWATER, MN

U.S. EPA ID#: MN POOC/ 7/877

Date: 4/30/91

Dear Mr. Swenson:

Attached is a copy of the screening site inspection report (SSIR) which has been prepared for the site listed above. This document is considered to be <u>final</u> and any changes and modifications based on comments made by your <u>agency</u> and the U.S. Environmental Protection Agency (U.S. EPA) during the 30 calendar day comment period have already been incorporated.

Because this is considered to be the final form of this document, this version of the SSIR may be distributed outside of your agency without prior notification and approval of U.S. EPA.

Please remember that the revised estimate of the Hazard Ranking System (HRS) score, which has already been furnished to your agency by FIT is still considered to be predecisional. Therefore, it should not be released. If you have any questions concerning the release of this information, please contact Ms. Jeanne Griffin, of my staff, at (312) 886-3007.

As was previously agreed upon, one set of original photographs for this SSIR has already been sent to your agency enclosed in the draft version of this SSIR. It is your agencies responsibility to see that these photographs are mounted in the photo logs enclosed in the final version of this SSIR. At this point the final version of the SSIR supersedes the draft version and the draft version of this SSIR should be removed from your agency files to ensure that the confidential draft version of this SSIR is not inadvertently released by your staff.

If you have any comments or questions, please contact Bill Messenger at (312) 353-1057.

Sincerely yours,

Thomas F. Kerolecker
Thomas F. Geishecker

Technical Support Section

Enclosure

cc: Bill Messenger

SIGNATURE PAGE
FOR
SCREENING SITE INSPECTION REPORT
FOR
T. O. PLASTICS
CLEARWATER, MINNESOTA
U.S. EPA ID: MND006171847
SS ID: NONE
TDD: F05-8811-003

PAN: FMN0188SA

Prepared	by:	Daniel Sullivan FIT Team Leader Ecology and Environment, Inc.	Date: _	7/30/91	
Reviewed	by:	Regina Bayer FIT State Coordinator Ecology and Environment, Inc.	Date: _	4/30/91	
Approved	by:	Jerome D. Oskvarek for OMO Jerome D. Oskvarek FIT Office Manager Ecology and Environment, Inc.	Date: _	4/20/91	**************************************

TABLE OF CONTENTS

Section		,	Page
1	INTRO	DDUCTION	1-1
2	SITE	BACKGROUND	2-1
	2.1	INTRODUCTION	2-1
•	2.2	SITE DESCRIPTION	2-1
	2.3	SITE HISTORY	2-1
3	SCREI	ENING SITE INSPECTION PROCEDURES AND FIELD	
	OBSE	RVATIONS	3-1
	3.1	INTRODUCTION	3-1
	3.2	SITE REPRESENTATIVE INTERVIEWS	3-1
	3.3	RECONNAISSANCE INSPECTION	3-1
	3.4	SAMPLING PROCEDURES	3-4
4	ANAL'	YTICAL RESULTS	4-1
	4.1	INTRODUCTION	4-1
	4.2	RESULTS OF CHEMICAL ANALYSIS OF FIT-	
		COLLECTED SAMPLES	4-1
5	DISC	USSION OF MIGRATION PATHWAYS	5-1
	5.1	INTRODUCTION	5-1
	5.2	GROUNDWATER	5-1
	5.3	SURFACE WATER	5-2
	5.4	AIR	5-3
	5.5	FIRE AND EXPLOSION	5-3
	5.6	DİRECT CONTACT	5-4
6	REFE	RENCES	6-1

Table of Contents (Cont.)

ppendix		Page
A	SITE 4-MILE RADIUS MAP	A-1
В	U.S. EPA FORM 2070-13	B-1
С	FIT SITE PHOTOGRAPHS	C-1
D	U.S. EPA TARGET COMPOUND LIST AND TARGET ANALYTE LIST QUANTITATION/DETECTION LIMITS	D-1
E	WELL LOGS OF THE AREA OF THE SITE	E-1

LIST OF FIGURES

igure		Page
2-1	Site Location	2-2
3-1	Site Features	3-3
3-2	Soil and Groundwater Sampling Locations	3-6

LIST OF TABLES

Table		Page
3-1	Addresses of Groundwater Sampling Locations	3-8
4 -1	Results of Chemical Analysis of FIT-Collected Soil Samples	4-2
4-2	Results of Chemical Analysis of FIT-Collected Groundwater Samples	4-4

INTRODUCTION

Ecology and Environment, Inc., Field Investigation Team (FIT) was tasked by the United States Environmental Protection Agency (U.S. EPA) to conduct a screening site inspection (SSI) of the T. O. Plastics (TOP) site under contract number 68-01-7347.

The site was initially identified during a Minnesota Pollution Control Agency (MPCA) inspection in August 1981. The site was evaluated in the form of a preliminary assessment (PA) that was submitted to U.S. EPA. The PA was prepared by Michael Connally of MPCA, and is dated January 7, 1986.

FIT prepared an SSI work plan for the TOP site under technical directive document (TDD) F05-8706-163, issued on June 5, 1987. The SSI work plan was approved by U.S. EPA on October 27, 1988. The SSI of the TOP site was conducted on June 20, 1989, under TDD F05-8811-003, issued on November 8, 1988.

The FIT SSI included interviews with site representatives, a reconnaissance inspection of the site, and the collection of six soil samples and two groundwater samples.

The purposes of an SSI have been stated by U.S. EPA in a directive outlining Pre-Remedial Program strategies. The directive states:

All sites will receive a screening SI to 1) collect additional data beyond the PA to enable a more refined preliminary HRS [Hazard Ranking System] score, 2) establish priorities among sites most likely to qualify for the NPL [National Priorities List], and 3) identify the most critical data requirements for the listing SI step. A screening SI will not have rigorous data quality ob-

jectives (DQOs). Based on the refined preliminary HRS score and other technical judgement factors, the site will then either be designated as NFRAP [no further remedial action planned], or carried forward as an NPL listing candidate. A listing SI will not automatically be done on these sites, however. First, they will go through a management evaluation to determine whether they can be addressed by another authority such as RCRA [Resource Conservation and Recovery Act].... Sites that are designated NFRAP or deferred to other statutes are not candidates for a listing SI.

The listing SI will address all the data requirements of the revised HRS using field screening and NPL level DQOs. It may also provide needed data in a format to support remedial investigation work plan development. Only sites that appear to score high enough for listing and that have not been deferred to another authority will receive a listing SI. (U.S. EPA 1988)

U.S. EPA Region V has also instructed FIT to identify sites during the SSI that may require removal action to remediate an immediate human health or environmental threat.

2. SITE BACKGROUND

2.1 INTRODUCTION


This section includes information obtained from SSI work plan preparation, the site representative interview, and a reconnaissance inspection of the site.

2.2 SITE DESCRIPTION

The TOP site is an active plastics facility where vacuum forming operations have taken place since 1958, and expandable polystyrene molding operations since 1975 (Engler, Helget, and Luhman 1989). The site is located on an approximately 12-acre parcel of land in the village of Clearwater, Minnesota, approximately 1,300 feet west-northwest of the Mississippi River, in Wright County (S1/2 sec. 35, T.123N., R.27W.), at 830 County Road 75 (see Figure 2-1). A 4-mile radius map of the TOP site and surrounding area is provided in Appendix A.

2.3 SITE HISTORY

The TOP site is owned and operated by T.O. Plastics of Minneapolis, Minnesota. T. O. Plastics began operating its plastics facility in Clearwater in 1958. Prior to the construction of the T.O. Plastics facility, the property was used for agricultural purposes. The main plant on-site, Plant 105, produces parts by vacuum forming. In the manufacturing process, acrylonitrilebutadiene styrene (ABS) pellets are heated and formed into pliable sheets. The sheets are placed in contact with the surface of a mold, and a vacuum system then draws air against the mold. The plastic material then cools and sets in the desired form.



SOURCE: Ecology and Environment, Inc. 1991; BASE MAPS: USGS, Clearwater, MN Quadrangle, 7.5 Minute Series, 1974.




FIGURE 2-1 SITE LOCATION

In 1975, T. O. Plastics constructed a second manufacturing facility, on property located south of Plant 105. This second facility, where the expandable polystyrene molding processes now take place, is called the bead plant. In this manufacturing process, polystyrene beads are subjected to steam processes, which expand the beads and allow the desired molding processes to occur (Engler, Helget, and Luhman 1989). The products are lightweight, styrofoam-like pieces used as cushioning material in packages.

According to MPCA records, two types of wastewater were discharged onto the ground of the site. One type was steam generator blow-down wastewater, with softening and descaling agents that may have contained small amounts of chromium. The other type was the wastewater discharged from a vacuum pump. The mixture of these wastewaters was discharged from Plant 105 to an on-site ditch. The wastewater then flowed to a low-lying field in the central area of the site, where it formed a pond. During an MPCA inspection in August 1981, the vacuum pump wastewater was found to have a "strong, questionable odor" (MPCA 1986).

No federal or state regulatory enforcement actions have occurred at the TOP site.

3. SCREENING SITE INSPECTION PROCEDURES AND FIELD OBSERVATIONS

3.1 INTRODUCTION

This section outlines procedures and observations of the SSI of the TOP site. Individual subsections address the site representative interview, reconnaissance inspection, and sampling procedures. Rationales for specific FIT activities are also provided. The SSI was conducted with minor alterations from the U.S. EPA-approved work plan because one of the two Clearwater municipal wells was unavailable for sampling. An on-site drinking water well was substituted.

The U.S. EPA Potential Hazardous Waste Site Inspection Report (Form 2070-13) for the TOP site is provided in Appendix B.

3.2 SITE REPRESENTATIVE INTERVIEWS

Daniel Sullivan, FIT team leader, conducted site representative interviews with Ken Engler, Bead Plant Manager, and Leonard Helget, Plant 105 Manager, on June 20, 1989. Present at both interviews were Violet Luhman, Operations Manager for T. O. Plastics, and Mike Phillips of FIT. The interview with Leonard Helget was conducted in the Plant 105 office at 8:35 a.m. The interview with Ken Engler was conducted in the bead plant office at 9:10 a.m. The interviews were conducted to gather information that would aid FIT in conducting SSI activities.

3.3 RECONNAISSANCE INSPECTION

Following the site representative interviews, FIT conducted a reconnaissance inspection of the TOP site and surrounding area in accordance with Ecology and Environment, Inc. (E & E), health and safety

guidelines. The reconnaissance inspection included a walk-through of the site to determine appropriate health and safety requirements for conducting on-site activities and to make observations to aid in characterizing the site. FIT also determined sampling locations during the reconnaissance inspection.


FIT team members arrived at the site at 8:23 a.m. on June 20, 1989. The reconnaissance inspection commenced at approximately 10:30 a.m. Violet Luhman accompanied FIT during the reconnaissance inspection.

Reconnaissance Inspection Observations. The TOP site is located in Clearwater, Minnesota, near the intersection of Highway 152 (County Road 75) and Highway 24 (State Highway 240) (see Figure 3-1 for locations of site features). Land use surrounding the site is primarily commercial and residential. The site is bordered on the north by Highway 24 and on the east by Porter Street. Land south of the site is owned by the Village of Clearwater, and contains a water tower, a municipal well house, and a community center. The site is bounded on the west by Highway 152.

There is no fence or other definition of the boundary between the site and adjacent property. Access to the TOP site is through a driveway off of Highway 24, which runs east of Plant 105. On-site roads, driveways, and parking lots have gravel surfaces. Photographs of the TOP site are provided in Appendix C.

The operations at Plant 105 involve the main plant building and four warehouses. A group of three warehouses is located immediately east of the main building and a fourth warehouse stands 100 feet northeast of the building. The main building is used for the vacuum molding operation; the warehouses are used for storage of equipment and raw materials. Plant 105 is L-shaped, with one wing oriented to the northeast and the major wing oriented southeast. Silos near the southeast corner of the building are used for storage of ABS pellets.

FIT observed water flowing from a pipe protruding from the main building's exterior wall near the silos. According to Helget, the water is used to cool vacuum pumps and is discharged to the ground (Helget 1989). The discharge water observed by FIT flowed into a ditch running south-southeast past the warehouses, east to a low-lying area southeast of the warehouses, and then to the central portion of the site, where it



formed a pond of standing water. FIT observed 55-gallon barrels inside and outside each of the three warehouses nearest Plant 105. Inside the warehouse closest to the building, approximately eight or nine barrels were observed. One was labeled perchloroethylene, one ethylene glycol, and the remaining barrels had no visible markings. Beside the eastern exterior wall of the third warehouse, FIT observed barrels that contained "cut-back" asphalt (Engler, Helget, and Luhman 1989). According to site representatives, T. O. Plastics may be using the asphalt on its roads at a future date.

The other T. O. Plastics facility, the bead plant, is located near the south boundary of the site and consists of a single square building where the company's polystyrene molding operations occur. A loading area, consisting of two elevated garage doors, is located on the south face of the building. A 270,000-gallon cooling pond is located approximately midway between the two plant buildings. T. O. Plastics uses the pond as a source of cooling water for molds and machinery in the bead plant and Plant 105 (Engler, Helget, and Luhman 1989). The pond is encircled by a barbed wire fence and a pump house is located east of the pond. The pond is lined with concrete and its water is constantly recycled. T. O. Plastics operators clean the pond every 2 to 3 years by pumping the pond water onto the ground. The concrete is then sprayed with a sealant and the pond is refilled (Helget 1989).

FIT observed two propane tanks on-site: one located approximately 50 feet north of Plant 105, and the other located approximately 170 feet east of the bead plant. The north tank was surrounded by a fence; the other tank was unfenced.

The site terrain sloped slightly downward toward the east, to the area in the center of the site where the discharge water collected. Site property east of the buildings and of the ponded water was vegetated with tall grasses and some trees.

3.4 SAMPLING PROCEDURES

Samples were collected by FIT at locations selected during the reconnaissance inspection to determine whether U.S. EPA Target Compound List (TCL) compounds and U.S. EPA Target Analyte List (TAL) analytes were present at the site. The TCL and TAL, with corresponding quan-

titation/detection limits, are provided in Appendix D. On June 20, 1989, FIT collected five surface soil samples and one potential background surface soil sample. Samples from one municipal well and one on-site drinking water well were also collected by FIT. A portion of each sample was provided to site representatives.

Soil Sampling Procedures. Surface soil sample S1 was collected from a loading area on the northeast wing of Plant 105 (see Figure 3-2 for soil and groundwater sampling locations). This location was chosen because of its proximity to potential runoff from the loading dock.


Surface soil sample S2 was collected in the low-lying central area of the site, at the western edge of the ponded discharge water. Surface soil sample S3 was collected on the south side of the bead plant, from a pile of soil below one of the doors of the loading area. This location was chosen because of its proximity to the loading dock.

Surface soil sample S4 was collected from an area between the silos and the ditch near the southeast corner of Plant 105. The location was chosen because of its proximity to the point where the wastewater discharges from Plant 105. Surface soil sample S5 was collected from a walkway between Plant 105 and the door of the warehouse where barrels were observed. This location was chosen because of its proximity to the barrels in the warehouse.

Surface soil sample S6 was collected off-site as a potential back-ground soil sample from a grassy area approximately 120 feet east of the site boundary. The background soil sample was collected to determine the representative chemical content of the soil in the area surrounding the site. The location was chosen because the ground surface appeared to be undisturbed.

Hand trowels were used to collect all soil samples. A hole 4 to 5 inches deep was excavated with the hand trowel. Sample material from the hole was transferred to a stainless steel bowl using the trowel. Samples were mixed in the bowl and then placed in sample bottles using the trowel (E & E 1987).

Standard E & E decontamination procedures were adhered to during the collection of all soil samples. The hand trowels and bowls were scrubbed with a solution of Alconox detergent and distilled water, and triple-rinsed with distilled water before the collection of each soil



sample (E & E 1987). All soil samples were packaged and shipped in accordance with U.S. EPA-required procedures.

As directed by U.S. EPA, soil samples S1, S2, S3, S4, S5, and S6 were analyzed under the U.S. EPA Contract Laboratory Program (CLP) for TCL compounds by American Analytical and Technical Services of Broken Arrow, Oklahoma, and for TAL analytes by Columbia Analytical Services of Longview, Washington.

Groundwater Sampling Procedures. One municipal well (RW1) and one on-site drinking water well (RW2) were collected to determine local groundwater characteristics.

The drinking water well sampling locations chosen were the nearest available sampling points to the TOP site (see Figure 3-2 for ground-water sampling locations). Sample RW1 was collected off-site from a well in the municipal well house, located approximately 200 feet south-southeast of the TOP site. The well depth was 94 feet (Minnesota Department of Health 1983). Sample RW2 was collected from an on-site well that is used as a source of drinking water at the bead plant. The well depth was 68 feet (Luhman 1989) (see Table 3-1 for addresses of groundwater sampling locations.)

A duplicate sample was collected at well location RW2, and a distilled water field blank was also collected, in accordance with U.S. EPA quality assurance/quality control (QA/QC) requirements. Groundwater samples RW1 and RW2 were collected from outlets that bypassed water treatment systems. For each sample, water was allowed to discharge from the outlet for approximately 10 minutes before samples were collected to insure that the sample source had been purged of standing water (E & E 1987). Both well samples were packaged and shipped in accordance with U.S. EPA-required procedures.

As directed by U.S. EPA, both well samples were analyzed under the U.S. EPA CLP for TCL compounds by Hazleton Laboratories, Inc., of Madison, Wisconsin, and by the U.S. EPA Central Regional Laboratory (CRL) of Chicago, Illinois; and for TAL analytes by the U.S. EPA CRL of Chicago, Illinois.

Table 3-1

ADDRESSES OF GROUNDWATER SAMPLING LOCATIONS

Sample	Address
RW1	NON-RESPONSIVE
	NON-
RW2	NON- RESPONSIV
	E

4. ANALYTICAL RESULTS

4.1 INTRODUCTION

This section includes results of chemical analysis of FIT-collected soil samples and groundwater samples for TCL compounds and TAL analytes.

4.2 RESULTS OF CHEMICAL ANALYSIS OF FIT-COLLECTED SAMPLES

<u>Soil Sampling Results</u>. Chemical analysis of FIT-collected soil samples revealed the presence of TAL analytes, including heavy metals, metals, and common soil constituents, and TCL compounds, including common laboratory artifacts, halogenated hydrocarbons, and pesticides (see Table 4-1 for complete soil sample chemical analysis results).

Groundwater Sampling Results. Chemical analysis of FIT-collected groundwater samples revealed the presence of TAL analytes, including heavy metals and TAL analytes commonly found in area substrate, and TCL compounds, including halogenated hydrocarbons and common laboratory artifacts (see Table 4-2 for complete groundwater sample chemical analysis results).

U.S. EPA CLP quantitation/detection limits used in the analysis of FIT-collected soil and groundwater samples are provided in Appendix D.

Table 4-1
RESULTS OF CHEMICAL ANALYSIS OF
FIT-COLLECTED SOIL SAMPLES

Sample Collection Information			Sample	Number		
and Parameters	S1	S2	S3	S4	s 5	\$6
Date	6/20/89	6/20/89	6/20/89	6/20/89	6/20/89	6/20/8
Time	1215	1230	1240	1310	1315	133
CLP Organic Traffic Report Number	EFP86	EFP87	EFP88	EFP89	EFP90	EFP9
CLP Inorganic Traffic Report Number	MEFF75	MEFF76	MEFF77	MEFF78	MEFF79	MEFF8
Compound Detected						
(values in µg/kg)						
Volatile Organics						•
methylene chloride						6
tetrachloroethene				20	98J	-
toluene	20Ј					_
Pesticides/PCBs						
Aldrin				8.5J		
4 , 4 ' - DDT						31
Analyte Detected						
(values in $\mu g/L$)	•	•				
aluminum	8,470	4,070	6,900	5,880	5,480	6,97
arsenic	1.8B	1.9B	1.88	1.6B	1.4B	2.1
parium	112	37.7В	62.7	58.8	48.6	86.
peryllium	0.65B		0.63B	0.56B	0.50B	0.51
cadmium	1.8				2.8	
calcium	3,560	5,940	7,700	13,300	9,740	2,34
chromium	17.8	11	10.5	10.3	11.6	8.
cobalt	6.68	5.3B	5.2B	4.48	6.0B	3.4
copper	30.6	9.3J	5.6J	13.8	12.5	5.6
ron	12,800	8,170	8,980	11,000	9,480	7,18
ead	33.9	4.3J+	6.5	23.3	46.3	11.
nagnesi um	3,020	2,780	3,850	3,910	3,590	1,20

Table 4-1 (Cont.)

Sample Collection Information			Sample	Number		
and Parameters	51	52	S3	\$4	S5	56
manganese	1,340J*	545J*	477J*	377J*	417J*	414J*
nickel	29.3J*	10.7J*	9.83*	8.7J*B	10.73*	6.7J*B
potassium	1,370	415B	716B	573B	525B	772B
selenium		0.23B		0.28B	0.27B	0.23B
sodium	90.5B	140B	180B	221B	66.1B	36.7B
thallium	0.56JB	0.29JB	0.25JB	0.34JB	0.35JB	0.21JB
vanadium	22.9	14.9	19.5	17.6	16.4	14.9
zinc	121	26	25.3	119	406	31.5

- Not detected.

CRDL.

COMPOUND QUALIFIER	DEFINITION	INTERPRETATION
J	Indicates an estimated value.	Compound value may be semiquantitative.
ANALYTE QUALIFIERS	DEFINITION Duplicate value outside QC protocols which indicates a possible matrix problem.	INTERPRETATION Value may be quantitative or semi- quantitative.
В	Value is real, but is above instrument DL and below	Value may be quantitative or semi-

quantitative.

Table 4-2
RESULTS OF CHEMICAL ANALYSIS OF
FIT-COLLECTED GROUNDWATER SAMPLES

Sample Collection Information		Sample	Number	
and Parameters	RW1	RW2	Duplicate	Blank
Date	6/20/89	6/20/89	6/20/89	6/20/89
Time	1100	1355	1355	1110
CRL Log Number	89FS22S11	89PS22S12	89FS22D12	89FS21R17
CLP Organic Traffic Report Number	EFP92	EFP93	EFP94	EFP95
Temperature (°C)	9	15	15	23
Specific Conductivity (µmhos/cm)	248	564	564	. 0
рн	7.08	7.07	7.07	6.94
Compound Detected			•	
(values in ug/kg)				
Volatile Organics				
tetrachloroethene	1J	·		
Semivolatile Organics				
di-n-octylphthalate				0.3J
Analyte Detected				
(values in µg/L)				
Darium	48	77.8	76.3	
calcium	87,800	96,00	95,00	
copper	8.5	19.8	20.7	124
iron	219			
lead	3		·	
magnesium	27,200	30,400	30,000	
nanganese	154	85	81.6	
nickel	52.9			16
sodium	11,400	19,100	18,700	

⁻⁻ Not detected.

Table 4-2 (Cont.)

COMPOUND QUALIFIER

DEFINITION

INTERPRETATION

J

Indicates an estimated value.

Compound value may be semiquantitative.

4

- Wastewater is discharged from Plant 105 and collects on the ground surface of an on-site field.
- The geology in the vicinity of the site indicates an area of unconsolidated, glacially derived deposits of sand, clay, and gravel.

According to area well logs (see Appendix E), the glacial drift deposits beneath the site extend to a depth of more than 90 feet. The bedrock underlying the glacial deposits consists of pre-Cambrian igneous and metamorphic rocks. The bedrock is undifferentiated and is not an aquifer, with the exception of areas of local faults and fractures (Kanivetsky 1978). It is believed that all wells in the area of the site draw from the glacial drift, making it the aquifer of concern (AOC) in the vicinity of the TOP site. Regional flow of groundwater in the undifferentiated drift aquifer is toward the east, toward the Mississippi River (Delin and Woodward 1984).

With the exception of the on-site well, the groundwater well nearest to the TOP site is the Clearwater municipal well #2, located approximately 200 feet south-southeast of the site. This well serves the approximately 429 residents of the town of Clearwater.

An additional population of approximately 642 persons, who reside within a 3-mile radius of the site and on the west side of the Mississippi River, is served by private wells drawing from the AOC. This estimate was obtained by counting residences on a United States Geological Survey (USGS) topographic map of the area (USGS 1974), and multiplying this figure by the 1980 Census average for Wright County of 3.15 persons per household (U.S. Bureau of the Census 1982).

These two population groups constitute the total potential target population for groundwater contamination from the TOP site. This target population includes approximately 1,071 persons who are served by municipal and private wells finished in the AOC.

5.3 SURFACE WATER

No surface water samples were collected during the SSI of the TOP site. The nearest surface water body is the Mississippi River, which is

1/5 mile east of the site and is used for recreation (Rockford Map Publishers 1984).

No direct overland surface water migration pathways were observed by FIT during the SSI. On-site drainage pathways appear to be toward the low-lying central portion of the site where the discharged wastewater was observed to collect.

5.4 AIR

A release of TCL compounds and/or TAL analytes to the air was not documented during the reconnaissance inspection of the TOP site. During the SSI, the HNu, oxygen meter, and explosimeter used by FIT did not detect concentrations above background levels on-site. In accordance with the U.S. EPA-approved work plan, further air monitoring was not conducted by FIT.

However, a potential exists for the release of contaminants to the air in the event of a fire (see Subsection 5.5). Potential air contamination targets include the approximately 1,955 persons residing within a 4-mile radius of the TOP site. This population was calculated in the same manner as described in Subsection 5.2, with the addition of house counts taken from maps of the areas of Sherburne and Stearns counties, which lie within the 4-mile radius. These figures were then multiplied by the 1980 census averages of 3.19 and 3.11 persons per household, respectively, for the two counties (U.S. Bureau of the Census 1982).

5.5 FIRE AND EXPLOSION

During the FIT reconnaissance inspection, no evidence of fire or explosive conditions was observed at the site. FIT instrument readings indicated no apparent potential for explosions at the site.

However, a potential exists for the release of contaminants in the event of a fire on-site. In pellet form, styrene-based plastics have a very low degree of toxicity. Once ignited they tend to burn rapidly and produce a dense, black smoke (Grayson and Eckroth 1978).

Potential targets of fire and explosion include the approximately 669 persons residing within a 2-mile radius of the TOP site. This population was calculated in the same manner described in Subsection 5.2, with additional house counts taken from maps of Sherburne and

Stearns counties, multiplied by the 1980 census averages of 3.19 and 3.11 persons per household, respectively, for those counties (U.S. Bureau of the Census 1982).

5.6 DIRECT CONTACT

According to federal, state, and local file information reviewed by FIT, and interviews with T. O. Plastics representatives, no documentation exists of an incident of direct contact with TCL compounds or TAL analytes at this site.

There is a potential for the public and for T. O. Plastics employees to come into direct contact with TAL analytes and TCL compounds detected at the site. The potential for direct contact is based on the following information.

- TAL analytes and TCL compounds were detected in surface soil samples.
- The site is not fenced.
- Land use surrounding the site is primarily commercial and residential.

The population within a 1-mile radius of the site is approximately 427 persons. This estimate was obtained using the same procedure described in Subsection 5.2.

6. REFERENCES

- Delin, G. N., and D. G. Woodward, 1984, Hydrogeologic Setting and the Potentiometric Surfaces of Regional Aquifers in the Hollandale Embayment, Southeastern Minnesota, 1970 to 1980, United States Government Printing Office.
- E & E, 1987, Quality Assurance Project Plan Region V FIT Conducted Site Inspections, Chicago, Illinois.
- Engler, Ken, Leonard Helget, and Violet Luhmen, June 20, 1989, bead plant Manager, Plant 105 Manager, and Operations Manager, T. O. Plastics, interview, conducted by Daniel Sullivan of E & E.
- Grayson, Martin, and David Eckroth, eds., 1978, <u>Kirk-Othmer Encyclopedia</u>
 of Chemical Technology, 3rd Edition, Volume 21, John Wiley and
 Sons, Inc.
- Helget, Leonard, October 27, 1989, Plant 105 Manager, T. O. Plastics, telephone conversation, contacted by Daniel Sullivan of E & E.
- Kanivetsky, Roman, 1978, Minnesota Geological Survey, Hydrogeologic Map of Minnesota.
- Luhman, Violet, June 28, 1989, Operations Manager, T. O. Plastics, letter, to Dan Sullivan of E & E.

Minnesota Department of Health, April 26, 1983, water well record for village of Clearwater, well number 190794.

MPCA, January 23, 1986, Potential Hazardous Waste Site Preliminary

Assessment and Executive Summary for T. O. Plastics, Clearwater,

Minnesota, U.S. EPA ID: MND006171847, prepared by Michael

Connally.

Rockford Map Publishers, 1984, Minnesota Travel and Recreation Guide.

U.S. EPA, February 12, 1988, Office of Solid Waste and Emergency Response, <u>Pre-Remedial Strategy for Implementing SARA</u>, Directive number 9345.2-01, Washington, D.C.

USGS, 1974, Clearwater, Minnesota Quadrangle, 7.5 Minute Series: 1:24,000.

4104:3

Α

APPENDIX A

SITE 4-MILE RADIUS MAP

SDMS US EPA Region V

Imagery Insert Form



Some images in this document may be illegible or unavailable in SDMS.

Please see reason(s) indicated below:

	Illegible due to bad source documents. Image(s) in SDMS is equivalent to hard copy. Specify Type of Document(s) / Comments:
82	
2	Includes COLOR or RESOLUTION variations. Unless otherwise noted, these pages are available in monochrome. The source document page(s more legible than the images. The original document is available for viewing at the Superfund Records Center. Specify Type of Document(s) / Comments:
	e e e e e e e e e e e e e e e e e e e
) : : (3	Confidential Business Information (CBI). This document contains highly sensitive information. Due to confidentiality, materials with succeinformation are not available in SDMS. For questions regarding viewing this document,, you may contact the EPA Superfund Records Manager. Specify Type of Document(s) / Comments:
v	Unscannable Material: Oversizedx or Format. Due to certain scanning equipment capability limitations, the document page(s) is not available SDMS. Specify Type of Document(s) / Comments:
9	FOUR OR FIFTEEN MILE RADIUS MAP
	Document is available at the EPA Region 5 Records Center. Specify Type of Document(s) / Comments:

В

APPENDIX B

U.S. EPA FORM 2070-13

\$EPA

EPA FORM 2070-13 (7-81)

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

L IDENTIFICATION			
OI STATE	02 SITE MUMBER DOOL 171847		

VLIA	PART 1 - SITE LOCATION AND INSPECTION INFORMATION					
IL SITE NAME AND LOCA						
O1 SITE MAKE Road common, or discretive name of soci			02 STREET, NOUTE NO., OR SPECIFIC LOCATION IDENTIFIER			
T.O. PLASTICS			830 County ROAD 75			
O. T. A. T. V. A. T. T.			MN 55320 WRIGHT			
CLEARWATE	R		111 00			
45.24.51.0	094 02 44.2	A PRIVATE DB.	■ A PRIVATE □ B. FEDERAL □ □ C. STATE □ D. COUNTY □ E. MUNICIPAL			
BL INSPECTION INFORMA	TO2 SITE STATUS	T 03 YEARS OF OPERATION				
6 ,20,89	■ ACTIVE	1958		UNKONOWN		
MONTH DAY YEAR	O NACTIVE	BEGINNING				
04 AGENCY PERFORMING INSPE		FAMILIA MARKET				
D.A. EPA B. E.P.A. CONTRACTOR ECOLOGY AND ENVIRONMENT D.C. MUNICIPAL D.D. MUNICIPAL CONTRACTOR						
DE. STATE DF. STATE	CONTRACTOR	Nome of firms	OTHER	Boschi		
OS CHEF INSPECTOR		OS TITLE		07 ORGANIZATION	(3121663-9415	
DANIEL SULLIVAN		CHEMICAL ENGINEER		E+E	. 1.5	
ON OTHER INSPECTORS		10 mue		11 ORGANIZATION E + E	12 TELEPHONE NO	
DEBORAH BARRETT		GEOLOGIST	GEOLOGIST		13121663-9415	
RONNIE GALMORE		TECHNICH	TECHNICIAN		13121663.9415	
MIKE PHILLIPS		GEOLOGIST		E.+E	13121663-9415	
KURT SIMS		EARTH SCIENTIST		E+E	1312163-9415	
				5	()	
13 SITE REPRESENTATIVES INTERVIEWED		14 TITLE	154009ESS 2901 E	AST 78TH STREET	16 TELEPHONE NO	
VIOLET LUHMAN		OPERATIONS MG	MINNEAPOLIS	MN 55425	16121854-2131	
LEONARD HELGET			1000 1		1612,558-2407	
KEN ENGLER		BEAD PLANT MGF	MANOO MEGI	MN 55320	16121558-6110	
					()	
			*		()	
					()	
17 ACCESS GAMED BY	18 TIME OF INSPECTION	19 WEATHER CONDITIONS	WEATHER CONDITIONS			
B PERMISSION 0823		AM PARTLY SUNNY, ~ 80°F, SOUTH WIND ~15-20 MPH PM SUNNY, ~ 90°F, SOUTH WIND ~ 20-25 MPH				
IV. INFORMATION AVAIL	LABLE FROM					
01 CONTACT		02 OF Moncy Ogurania			03 TELEPHONE NO	
RON SWENSON		MINNESOTA POLLUTION CONTROL AGENCY			16121297-1793	
04 PERSON RESPONSIBLE FOR SITE INSPECTION FORM		OS AGENCY OS	ORGANIZATION		OB DATE	
DANIEL SULLIVAN		U.S. EPA	ENVIRONMENT	(312) 663-9415	10,13,89	

\$EPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 2-WASTE INFORMATION

L IDENTIFICATION

01 STATE 02 SITE NAMES

MN DOOG 171847

	TATES, QUANTITIES, AI	02 WASTE QUANTIT	Y AT SITE	03 WASTE CHARACT	ERISTICS (Check of the	esold.		Minute Maria
BA SOUD DE SLURRY DB POWDER, FINES BF LOUID DC SLUDGIE D & GAS		1048 UNKNOWN		B A TOXIC DE SOLU O B CONNOSNE DE PREE U C RADIOACTIVE D Q FLAN BI D PERSISTENT B N GART		CTIOUS DI EXPLOSIVE		NE ATOLE
U U Unica	(Specify)	NO OF DRUMS						
IIL WASTE T	YPE							
CATEGORY	SUBSTANCE	HAME	OI GROSS AMOUNT	02 UNIT OF MEASURE	03 COLIMENTS			
SLU	SLUDGE							
OLW	OLY WASTE							
SOL	SOLVENTS				UNK	NAV	VAL	
PS0	PESTICIDES				ONK	1400	414	
occ	OTHER ORGANIC C	HEMICALS						
NOC .	INORGANIC CHEMI	CALS						
ACO	ACIOS							
BAS	BASES							
MES	HEAVY METALS				-			
IV. HAZARD	OUS SUBSTANCES (540)	Appendix for most frequently	colod CAS Runbora					
01 CATEGORY	02 SUBSTANCE	NAME	03 CAS NUMBER	04 STORAGE/DIS	POSAL METHOD	05 CONCE	NTRATION	DE MEASURE D CONCENTRATED
	C			1				
	2FF	7 2F	CTION	4				
					•			
						-		
						-		
						+		
				1		+		
						-		
•						-		
1								
							1	
-								
V. FFFDSTC	OCKS (See Asserted to CAS No.							
CATEGORY			02 CAS MUMBER	CATEGORY	O1 FFFDS	TOCK NAME		02 CAS MUVSES
The state of the s	2/7/10/20/20/20/20		Or CHO HOMEON	FDS			_	02 CAS MOVSE
FDS	N/A						_	
FDS				FOS				
FDS				FDS				
FDS				FOS				
	S OF INFORMATION (stote Mes, cample analysis.	· Maron				
STATE	(MP.CA) FIL	(3)		201				
E COLOG	Y AND ENVI	RONMEN	FILES, F	REGION I.				

€FPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

LIDENTIFICATION
OF STATE OF STITE MANGER
MAN DOOK 171 047

PART 3- DESCRIPTION OF H	AZARDOUS CONDITIONS AND INCIDENT	rs [min]D	200111841
IL HAZARDOUS CONDITIONS AND INCIDENTS			
01 B A GROUNDWATER CONTAMINATION ~ 1,071 03 POPULATION POTENTIALLY AFFECTED: ~ 1,071 SEE SECTION 5.2	02 D OBSERVED (DATE:] 04 NARRATIVE DESCRIPTION	■ POTENTIAL	O ALLEGED
OIDS SURFACE WATER CONTAMINATION N/A OIDS SURFACE WATER CONTAMINATION N/A SEE SECTION 5.3	02 D OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	O POTENTIAL	□ ALLEGED
OI BC. CONTAMINATION OF AR O3 POPULATION POTENTIALLY AFFECTED: ~1,955 SEE SECTION 5.4	02 () OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	POTENTIAL	D ALLEGED
01 8 D. FREZEXPLOSNÉ CONDITIONS 03 POPULATION POTENTIALLY AFFECTED: SEE SECTION 5.5	02 CJ OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	POTENTIAL	□ ALLEGED
01 DE DRECT CONTACT 03 POPULATION POTENTIALLY AFFECTED: 427 SEE SECTION 5.6	02 D OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	■ POTENTIAL	O ALLEGED
SEE SECTION 4	02 @ OBSERVED (DATE: 6-20-89 04 NARRATIVE DESCRIPTION	O POTENTIAL	O ALLEGED
61 B G. DRINKING WATER CONTAMINATION ~1,071 63 POPULATION POTENTIALLY AFFECTED: ~1,071 SEE SECTION 5.2	02 D OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	■ POTENTIAL	O ALLEGED.
OI B H. WORKER EXPOSUREMUNY ON WORKERS POTENTIALLY AFFECTED	02 C) OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	B POTENTIAL	D ALLEGED
OI BL POPULATION EXPOSUREMUNTY AFFECTED: ~ 1,955 SEE A, C, D ABOVE	02 CJ OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	■ POTENTIAL	D ALLEGED

\$EPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS

L IDENTIFICATION
OI STATE OF SITE MANSER
MN DOGG 171847

IL HAZARDOUS CONDITIONS AND INCIDENTS revenue
01 B J DAMAGE TO FLORA 04 NARRATIVE DESCRIPTION 02 D OBSERVED (DATE:
POTENTIAL EXISTS FOR TCL COMPOUNDS AND TAL ANALYTES TO AFFECT FLORA.
01 B K DAMAGE TO FAUNA 02 D OBSERVED (DATE:
POTENTIAL EXISTS FOR TCL COMPOUNDS AND TAL ANALYTED TO AFFECT FAUNA.
01 B L CONTAMINATION OF FOOD CHAIN 02 D OBSERVED (DATE:
POTENTIAL EXISTS IF CONTAMINATED FAUNA ARE CONSUMED.
O1 B M UNSTABLE CONTANNENT OF WASTES O2 DOBSERVED (DATE: 6.20.89) D POTENTIAL O3 POPULATION POTENTIALLY AFFECTED: O4 NARRATIVE DESCRIPTION VACUUM PUMP COOLING WATER DISCHARGED. TO THE GROUND OUTSIDE OF BUILDING.
01 D IN DAMAGE TO OFFSITE PROPERTY 02 DOBSERVED (DATE:
None WAS NOTED
O1 D O CONTAMBATION OF SEWERS, STORM DRAINS, WATPS 02 DOBSERVED (DATE:) D POTENTIAL D ALLEGED O4 NARRATIVE DESCRIPTION
01 D P. ILLEGAL/UNAUTHORIZED DUMPING 02 D OBSERVED (DATE:
NONE WAS NOTED.
OS DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL, OR ALLEGED HAZARDS
NONE WAS NOTED
ML TOTAL POPULATION POTENTIALLY AFFECTED: ~ 1,955
IV. COMMENTS
SITE IS A PLASTICS FACILITY WHICH DOES VACUUM FORMING AND EXPANDABLE POLYSTYRENG MOLDING
CLEARWATER MUNTCIPAL WELL LOCATED - 200 FEET SSE OF STIE.
V. SOURCES OF INFORMATION (Cire specific informacios e g., assert less, sample contysis, reportly
STATE (MPCA) FILES ECOLOGY AND ENVIRONMENT FILES, REGION I. SSI CONDUCTED 6-20-89.

€EPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION

L IDENTIFICATION OI STATE OF SITE NUMBER

MN D006171847 **PART 4-PERMIT AND DESCRIPTIVE INFORMATION** IL PERMIT INFORMATION OI TYPE OF PERMIT ISSUED OZ PERMIT HUMBER 03 DATE ISSUED | 04 EXPIRATION DATE | 05 COMMENTS OA MPDES De uc DC AR DD. RCRA DE BORA INTERIM STATUS DF. SPCC PLAN DG. STATE SPOOTS DH. LOCAL GHOOM DL OTHER BOOCH BJ. NONE BL SITE DESCRIPTION 02 AMOUNT O4 TREATMENT (Check of their world) 03 UNIT OF MEASURE 05 OTHER OI STORAGE/DISPOSAL (Cred at that work) ~ 270 000 GALLONS B A SURFACE IMPOUNDMENT D A INCENERATION (NON-CONTACT COOLING WATER) A BUILDINGS ON SITE D B. PLES ☐ 8. UNDERGROUND INJECTION D. C. DRUMS, ABOVE GROUND D. C. CHEMICALPHYSICAL E) D TANK, ABOVE GROUND D. BIOLOGICAL DIE TANK BELOW GROUND 06 AREA OF SITE ☐ E. WASTE OIL PROCESSING D.F. LANDFILL ☐ F. SOLVENT RECOVERY ~12 D G. LANDFARM G. OTHER RECYCLING/RECOVERY OH OPEN DUMP -DH. OTHER_ O LOTHER_ 07 COMMENTS SITE IS UNFENCED WITH THE EXCEPTION OF A PROPANE TANK AND THE CONCRETE POND. LAND USE SURROUNDING THE SITE IS PRIMARILY COMMERCIAL AND RESIDENTIAL. IV. CONTAINMENT OI CONTAMBLENT OF WASTES (CHICA ONE) D A ADEQUATE, SECURE D B. MODERATE C. INADEQUATE, POOR I) D. INSECURE, UNSOUND, DANGEROUS OZ DESCRIPTION OF DRUMS, DIVING, LINERS, BARRIERS, ETC. POND IS PERIODICALLY SPRAYED WITH A SEALANT VACUUM PUMPAWATER DISCHARGED TO GROUND OUTSIDE THE BUILDING V. ACCESSIBILITY OI WASTE EASILY ACCESSIBLE: WYES DINO 02 COMMENTS SITE IS UNFENCED WITH RESIDEMIAL / COMMERCIAL AREAS NEARBY.

VL SOURCES OF INFORMATION (On specific subsection, or a state that, sample analyses, reported

STATE (MPCA) FILES

ECOLOGY AND ENVIRONMENT FILES. REGION V.

SSI CONDUCTED 6-20-89.

\$EPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT WATER DEMOGRAPHIC AND ENVIRONMENTAL DATA

LIDENTIFICATION
OI STATE OZ SITE MANGEA
MN DOOG 17 847

B. DRINKING WATER SUPPLY				-	<u> </u>	_	
OI TYPE OF DRONCHS SUPPLY		02 STATUS					O DISTANCE TO BITE
SURFACE	E METT	ENDANGERE	D AFFECTED	1	MONITORED		200 FEET
COMMUNTY A D	8.0	A.O	8. 0		C. .		~ 200
NON-COUNTRY C. D	0.0	0. 🔾	EO	UNKA	I O		1. ~ 3/4 [10]
ML GROUNDWATER							
O1 GAOLHOWATER USE IN VICINITY (Own	the factor						
D & GMLY SOURCE FOR DRINGING	B B. DRINKING (Other courses overlid COMMERCIAL IN The other center course	DUSTRIAL PRRIGATIO	firmed or		MOUSTRIAL BRAIGA	TION	D D NOT USED, UNUSEABLE
02 POPULATION SERVED BY GROUND W.	~1,071	-	03 DISTANCE TO N	EARES	T DRINKING WATER	WELL_	ON-SITE M
04 DEPTH TO GROUNDWATER	OS DIRECTION OF GRO	OUNDWATER FLOW	OS DEPTH TO AGUS	FER	07 POTENTIAL YE	ما	OR BOLE SOURCE AGUIFER
~50	EAST	τ !	~ 50		UNKNOWN		DYES BNO
				_(40)	Olektrachila	_{god)	
CLEARWATER MUNICIPAL PRIVATE WELLS WITHIN							
10 REDWAGE AREA			11 DISCHARGE ARE	A		_	
YES COMMENTS			TES COM	MENT	5	- 1	MISSISSIPPI RIVER
D NO PRECIPI	TATION				DISCHARGE	To II	HELLELING, HELLET
			D NO				133133181 141000
IV. SURFACE WATER			D HO			_	1331331971 141000
IV. SURFACE WATER 01 SURFACE WATER USE (Check and 0 A RESERVOIR RECREATION DRINKING WATER SOURCE	D B. PRIGATIO	N, ECONOMICALLY		ERCM	L, INDUSTRIAL		D. NOT CUPRENTLY USED
OI SUNFACE WATER USE (Check and	☐ B. FRIGATION			ERCM			
O1 SUNFACE WATER USE (Owed and B A RESERVOIR RECREATION DRINKING WATER SOURCE	☐ B. FRIGATION			ERCU		0	
O1 SUFFACE WATER USE (Over) and B A RESERVOIR RECREATION DRUNKING WATER SOURCE O2 AFFECTED/POTENTIALLY AFFECTED IN NAME:	B. FREGATION BMPORTAN BOOKS OF WATER			ERCM	L, INDUSTRIAL AFFECTED	0	D. NOT CUPPRENTLY USED DISTANCE TO SITE
O1 SUNFACE WATER USE (Does and A RESERVOR RECREATION DEBNICHE WATER SOURCE O2 AFFECTED/POTENTIALLY AFFECTED	B. FREGATION BMPORTAN BOOKS OF WATER			ERCM	AFFECTED	0	D. NOT CURRENTLY USED
O1 SUFFACE WATER USE (Over) and B A RESERVOIR RECREATION DRUNKING WATER SOURCE O2 AFFECTED/POTENTIALLY AFFECTED IN NAME:	B. FREGATION BMPORTAN BOOKS OF WATER			ERCM	AFFECTED O	0	D. NOT CUPPRENTLY USED DISTANCE TO SITE
OI SUNFACE WATER USE JONES AND DEBNICHE WATER SOURCE OR AFFECTED/POTENTIALLY AFFECTED IN NAME: MISSISSIPPI RIVE	D B. PRIGATION BAPORTAN			ERCU	AFFECTED	0	D. NOT CUPPRENTLY USED DISTANCE TO SITE
OI SUNFACE WATER USE JONES AND PROPER OF A PRESERVOIR RECREATION DESIREMENTS OF A PRECIDENT PROPER OF A PROPER OF	D B. PRIGATION BAPORTAN				AFFECTED O O	0	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE
O1 SUFFACE WATER USE (Overland B A RESERVOIR RECREATION DRINKING WATER SOURCE O2 AFFECTED/POTENTIALLY AFFECTED II NAME: M 1 S S 1 S S I PP I RIVE V. DEMOGRAPHIC AND PROPER 01 TOTAL POPULATION WITHIN	D B. PRIGATION BAPORTAN	THREE (3			AFFECTED O O D D D D D D D D D D D	D EST POP	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE
OI SUFFACE WATER USE JONES AND PROPER OF TOTAL POPULATION WITHIN ONE [1] SMILE OF SITE TO A PROPER OF THE CARD PROPERTY OF THE CA	D B. PRINGATION BAPORTAN BOOKS OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE (3	B) MILES OF SITE	002	AFFECTED O DISTANCE TO HEAR	D EST POP	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE
OI SUNFACE WATER USE JONES AND PROPERTY OF STEEL	D B. PRINGATION BAPORTAN BOOKS OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE (3	B) MILES OF SITE	002	AFFECTED O O D D D D D D D D D D D	D EST POP	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE
OI SUNFACE WATER USE JONES AND PROPERTY OF STEEL	D B. PREGATION SWPORTAN BOOKS OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE (3	B) MILES OF SITE 1195 0 OF PERSONS	O2	AFFECTED OSTANCE TO NEAR	EST POP	D. NOT CUPPRENTLY USED DISTANCE TO SITE ~ 1300 FEE
OI SUNFACE WATER USE JOHN AND DRINKING WATER SOURCE OR AFFECTED/POTENTIALLY AFFECTED IN NAME: MISSISSIPPI RIVE V. DEMOGRAPHIC AND PROPER OI TOTAL POPULATION WITHIN ONE (1) IMILE OF SITE A 427 NO OF PERSONS OS POPULATION WITHIN VICINITY OF SITE OS POPULATION WITHIN VICINITY OF SITE	D B. FRRIGATION BNPORTAN BODIES OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE ()	B) MILES OF SITE 1195 0 OF PURIONS 04 DISTANCE TO M	DEANES days. 6	DISTANCE TO NEAR	EST POP	D. NOT CUPPRENTLY USED DISTANCE TO SITE ~ 1300 FEE
OI SUNFACE WATER USE FOND AND B A RESERVOIR RECREATION DESIREMENTS WATER SOURCE OR AFFECTED/POTENTIALLY AFFECTED IN AME: MISSISSIPPI RIVE V. DEMOGRAPHIC AND PROPER OI TOTAL POPULATION WITHIN ONE (1) MILE OF SITE A 427 NO OF PERSONE OS POPULATION WITHIN VICINITY OF SITE T. O. PLASTICS	D B. PREGATION BODIES OF WATER TY INFORMATION TWO (2) MILES OF SITE B. ~ (6.9) TO OF PERSONS [2] MILES OF SITE [2] INLES OF SITE [3] LOCATED IN	THREE (3 C	B) MILES OF SITE 1195 D OF PERSONS ON DESTANCE TO M	DEANES WAT	AFFECTED OSTANCE TO NEAR OT OFF-SITE BURLDING ~ 50	EST POP	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE LITE IND
OI SUNFACE WATER USE FOND AND B A RESERVOR RECREATION DENNING WATER SOURCE OR AFFECTED/POTENTIALLY AFFECTED IN NAME: MISSISSIPPI RIVE V. DEMOGRAPHIC AND PROPER OI TOTAL POPULATION WITHIN ONE (1) IMILE OF SITE A 427 NO OF PERSONS OS POPULATION WITHIN VICINITY OF SITE T. O. PLASTICS LAND USE S	D B. FREIGATION BODIES OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE (3 C	B) MILES OF SITE 1195 D OF PERSONS ON DESTANCE TO M	DEANES WAT	AFFECTED OSTANCE TO NEAR OT OFF-SITE BURLDING ~ 50	EST POP	D. NOT CURRENTLY USED DISTANCE TO SITE ~ 1300 FEE LITE IND
OI SUNFACE WATER USE FOND AND B A RESERVOIR RECREATION DESIREMENTS WATER SOURCE OR AFFECTED/POTENTIALLY AFFECTED IN AME: MISSISSIPPI RIVE V. DEMOGRAPHIC AND PROPER OI TOTAL POPULATION WITHIN ONE (1) MILE OF SITE A 427 NO OF PERSONE OS POPULATION WITHIN VICINITY OF SITE T. O. PLASTICS	D B. FREIGATION BODIES OF WATER TY INFORMATION TWO (2) MILES OF SITE B	THREE (3 C	B) MILES OF SITE 1195 D OF PERSONS ON DESTANCE TO M	DEANES WAT	AFFECTED OSTANCE TO NEAR OT OFF-SITE BURLDING ~ 50	EST POP	DISTANCE TO SITE ~ 1300 FEE LUATION LITE (mg)

\$EPA

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT

LIDENTIFICATION OI STATE OZ SITE MUMBER

MN D006171847 PART 5 - WATER, DEMOGRAPHIC, AND ENVIRONMENTAL DATA VL ENVIRONMENTAL INFORMATION OI PERMEABILITY OF UNSATURATED ZONE (Check and □ A 10-6 - 10-6 cm/sec ■ 8, 10-4 - 10-6 cm/sec □ C, 10-4 - 10-3 cm/sec □ D GREATER THAN 10-3 cm/sec OZ PERMEABILITY OF BEDROCK (Check and □ B. RELATIVELY IMPERMEABLE □ C. RELATIVELY PERMEABLE □ D. VERY PERMEABLE (10⁻² - 10⁻⁴ covinc) (10⁻² - 10⁻⁴ covinc) COM POR 10-4 CONSIGN 04 DEPTH OF CONTAMNATED SOIL ZONE 05 SOIL pH >90 UNKNOWN m UNKNOWN DE NET PRECIPITATION OT ONE YEAR 24 HOUR RAINFALL OB SLOPE SITE SLOPE DIRECTION OF SITE SLOPE, TERRAIN AVERAGE SLOPE 2.25 EAST 09 PLOCO POTENTIAL DI SITE IS ON BARRIER ISLAND, COASTAL HIGH HAZARD AREA, RIVERINE FLOODWAY YEAR FLOODPLAIN 11 DISTANCE TO WETLANDS IS NOT ANNUAL 12 DISTANCE TO CRITICAL HABITAT por andargored to ESTUARINE OTHER ENDANGERED SPECIES: 13 LANDUSE IN VICINITY DISTANCE TO: AGRICULTURAL LANDS PRIME AG LAND RESIDENTIAL AREAS, NATIONALISTATE PARKS, PORESTS, OR WILDLIFE RESERVES COMMERCIAL SIDUSTRIAL AG LAND N/A ~400 FEET ~ 150 FEET

14 DESCRIPTION OF SITE IN RELATION TO SUPROUNDING TOPOGRAPHY

APPENDIX A. SEE

VIL SOURCES OF INFORMATION ICH MARK INFORMACIO, O S. MAR GOL, MARKE ANGUL MARKET

ECOLOGY AND ENVIRONMENT FILES, REGION I. USGS TOPOGRAPHIC MAP, CLEARWATER, MN QUAD.

-	-	-
==		
	Street, or other Designation of the last o	

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 6 - SAMPLE AND FIELD INFORMATION

L	DENT	TECATION
01	MN	DØ06171847

	N N	OI NUMBER OF	TOZ SAMPLES SENT TO	OJ ESTMATED DATE			
SAMPLE TYPE		SAMPLES TAKEN		RESULTS AVAILAB			
GROUNDWATER		2	TCL - HAZLETON LABS MADISON, WI TCL - US EPA CENTRAL REGIONAL LAB CHICAGO, IL	IN			
SURFACE WATER			TAL - U.S. EPA CEMPAL REGIONAL LAB CHICAGO, IL	IN			
WASTE							
AR							
RUNOFF							
SPIL .			Tel - American Anniversa - Tell Cie Tonica Adead au				
SOL		6	TCL - AMERICAN ANALYTICAL + TECH. SVS. DROGEN ARROW, OK TAL - COLUMBIA ANALYTICAL SERVICES LONGVIEW, WA	IN			
VEGETATION			1				
OTHER							
IL FIELD MEASUR	EMENTS TAI	KEN					
1 TYPE		02 COMMENTS					
HNu		NO READIN	NGS ABOVE BACKGROUND				
O2 /EXPLOS	IMETER						
RAD - MINI			-				
DRAEGER PI			•				
V. PHOTOGRAPH			CHICAGO				
OI TYPE B GROUP			filtrane of aggregation or individual				
BYES DNO	ECOL	OGY AND EN	VIRONMENT CHICAGO				
V. OTHER FIELD D	ATA COLLEC	CTED Andrews	oped .				
N/A		¥2					
IA							
VI. SOURCES OF I	NFORMATIO	N par specific references, a	g , state Bas, sample analysis, reported				
			7 FILES, REGION I.				
22T COND	UCTED	6-20-8	37				

\$EPA	F	SITE INSPI	ARDOUS WASTE SITE COTION REPORT HER INFORMATION LIDENTIFICATION OI STATE OF STAT		
L CURRENT OWNER(S)			PARENT COMPANY parkage		
T.O. PLASTICS		R38MUM 8+0 50	OF NAME N/A		OR D+8 HUNSER
2901 EAST 78TH S		04 SIC CODE	10 STREET ADDRESS (F 0 des, MOT, mc)		11 SC COOE
MINNEAPOLIS		55425	12 CITY	13 STATE	14 ZIP COOE
DI KAME		02 0+8 NUMBER	OR NAME		09 D+8 NUMBER
DISTREET ADDRESS (P.O. Son, NO.P. on.)		04 SIC CODE	10 STREET ADDRESS (P.O. Box, MO P. or.)		11 SC COOE
os criv	OS STATE	07 2F COOE	12 OTY	13 STATE	14 ZP CODE
OI NAME		02 D+8 NUMBER	OS NUME		09 D+8 MARSER
D3 STREET ADDRESS (P.O Box, N/D F, oc.)		04 SIC CODE	10 STREET ADDRESS (P.O. Sec. NO F. et.)		115C C00€
os aty	D6 STATE	07 ZP COOE	12 CITY	13 STATE	14 ZP COOE
DI KAKE		02 D+8 MUMBER	OR NAME		09 D+8 NUMBER
03 STREET ADDRESS (P.O. Box, AFD F, oc.)		04 SIC CODE	10 STREET ADDRESS (P.O Sec. NO.F. OC.)		115C COOE
OS CITY	OG STATE	07 29° COO€	12 0174	13 STATE	14 ZIP CODE
BL PREVIOUS OWNER(S) and most record	-	<u> </u>	IV. REALTY OWNER(S) or applicable, for	med record find	
N/A		G2 D+8 MUMBER	OI NAME	*	02 D+8 MARKER
03 STREET ADDRESS (P.O. dec, MO 1, sec.)		04 SIC COOE	03 STREET ADORESS (P.O. Soc. AFD C. oc.)		04 SC COOE
05 CITY	OBSTATE	07 2P COOE	os arry	OS STATE	07 ZP CODE
O1 MANE		02 0+8 HUMBER	OT NAME		02 D+8 M.MBER
03 STREET ADDRESS P.O Bu, MOF, OC.)		64 SIC CODE	03 STREET ADDRESS (F.O. Sec. AFD F, oc.)		04 9C COO€
06 CITY	OS STATE	OT ZIP COOE	05 CITY	06 STATE	07 ZP COOE
O1 KAME		G2 D+8 MUMBER	OI MANE		02 D+8 NUMBER
03 STREET ADDRESS (P.O Day, NOV. ac.)		04 SIC CODE	O3 STREET ADDRESS P.O Su. MD P. CL.		04 SC COOE
OSCITY	OS STATE	67 25° COOE	06 CITY	DO STATE	07 ZIP COOE
V. SOURCES OF INFORMATION CO.	pecific autoriscon	et an er man who	E. Ayony		
ECOLOGY AND ENVIRON	0-20	FILES, R	EGION Y.		

EPA FORM 2070-13 (7-81)

≎EPA		SITE INSPE	ARDOUS WASTE SITE CTION REPORT ATOR INFORMATION	OI STATE O	OI STATE OF SITE NAMES MN DOOG 171847	
IL CURRENT OPERATOR	of the bound		OPERATOR'S PARENT COMPA	MY Funkany		
SAME AS OWNER		02 D+8 MUNISER	N/A		110+8 MLANGER	
D3 STREET ACCRESS (P O Box, AVD F, ok.)		04 SC COOE	12 STREET ADDRESS P 0 ALL ATD P. ME	· ·	13 SIC COOE	
05 CITY	OS STATE	07 ZP COOE	14 CITY	15 STATE	14 ZIP CODE	
OG YEARS OF OPERATION OR NAME OF OW	NER					
ML PREVIOUS OPERATOR(S)	care link, provide an	y I allowed have arrest	PREVIOUS OPERATORS' PARE	NT COMPANIES	T concessing	
N/A		02 D+8 NUMBER	10 NAME		110+8 NUMBER	
03 STREET ACCRESS (P O Bac, MD F, arc.)		04 SIC CODE	12 STREET ADDRESS (P O Box, NFD 4, or.	,	13 SC 000E	
05 CITY	OS STATE	07 ZIP COOE	14 CTY	15 STATE	16 28 CODE	
OG YEARS OF OPERATION OR NAME OF OW	MER DURING THE	S PERIOD				
OI NAME		02 D+8 MANBER	10 NAME		110+8 NUMBER	
03 STREET ACCRESS (P.O. But, MOF, ML)		04 SIC CODE	12 STREET ADDRESS (F.O Box, NVD+, oc.,	,	13 SC COOE	
OS CITY	06 STATE	07 ZP COOE	14 CITY	15 STATE	14 ZP COOE	
DE YEARS OF OPERATION DO NAME OF OW	NER DURING THE	S PERIOD .	1-			
01 NAME		02 D+8 NUMBER	10 NAME		11 D+8 HUMBER	
03 STREET ADDRESS (P.O. Onc. NOV. onc.)		04 SC CODE	12 STREET ADORESS (F.O. Day, APD F, or.	,	13 SC COOE	
OS CETY	OS STATE	07 2# COOE	14 CITY	15 STATE	14 ZIP CODE	
OR YEARS OF OPERATION OR NAME OF OW	NER DURING THE	S PERIOD				
IV. SOURCES OF INFORMATION (CA)	profit references.	g., state Blue, earspite analys	à. reportel			
ECOLOGY AND ENV			, REGION I.		*	

	PO	TENTIAL HAZ	ARDOUS WASTE SITE	LIDENTIFK		
\$EPA		SITE INSPE	SITE INSPECTION REPORT GENERATOR/TRANSPORTER INFORMATION 01 STATE 02 STEEL 03 STEEL 04 STATE 02 STEEL 03 STEEL 04 STATE 02 STEEL 04 STATE 02 STEEL 04 STATE 03 STEEL 04 STATE 03 STEEL 04 STATE 04 STAT			
IL ON-SITE GENERATOR						
N/A	O:	2 D+B NUMBER				
Q) STREET ADDRESS PO But NOT, on 1		04 SIC COO€				
osaty	OS STATE O	7 20° COO€	•			
EL OFF-SITE GENERATOR(S)						
N/A	0	2 D+ S NUMBER	O1 NAME	ľ	D2 D+8 NUMBER	
O3 STREET ADDRESS (P.O. Box, MOF, or.)		04 SIC COO€	03 STREET ADDRESS # 0 Am. WOF, mc 1		04 SIC COOE	
DS CITY	06 STATE O	7 ZIP COOE	OS CITY	OG STATE	07 ZIP COOE	
OT RAME	0	2 D+8 NUMBER	O1 NAME		02 D+B NUMBER	
03 STREET ADDRESS (P.O. Bus, MOF, ok.)		04 SIC COO€	03 STREET ADDRESS # 0 844, MD 0, ML		04 SC COOE	
OS CITY	DE STATE O	7 ZIP CODE	os atr	O6 STATE	07 2P COOE	
IV. TRANSPORTER(S)						
N/A	0	2 D+B NUMBER	O1 NAME		02 D+8 NUMBER	
03 STREET ADDRESS P.O. Son, MOV. on.)		04 SIC COOE	O3 STREET ADORESS (F O. Box, NYD F, onc.)		04 SIC CODE	
OS CITY	OS STATE O	7 20° COOE	06 CITY	OS STATE	07 2P COOE	
01 NAME	0	2 D+8 NUMBER	OI NAME		02 D+8 NUMBER	
03 STREET ADDRESS (F.O Box, AFD4, ox.)		04 SIC COOE	03 STREET ADDRESS (F.O dos, MOF, oc.)		04 SC COOE	
OS CITY	DE STATE O	7 ZIP CODE	os atry	OS STATE	07 ZP CODE	
V. SOURCES OF INFORMATION	Car process ordered and a second	, state Stat, sample analysi	Land			
ECOLOGY AND EN					/	
SSI CONDUCTED						
302	_		*			

EPA FORM 2070-13 (7-41)

-		_	_
479		\mathbf{n}	
			-
0	-		

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 10 - PAST RESPONSE ACTIVITIES

L IDENTIFICATION				
MN STATE	DO06171847			

VERA	PART 10 - PAST RESPONSE ACTIVITIES	MN 0006171847
IL PAST RESPONSE ACTIVITIES		
01 D.A. WATER SUPPLY CLOSED 04 DESCRIPTION N/A	O2 DATE	03 AGENCY
01 D B. TEMPORARY WATER SUPPLY PRO 04 DESCRIPTION N/A	OVIDED 02 DATE	03 AGENCY
01 D.C. PERMANENT WATER SUPPLY PRO 04 DESCRIPTION N/A	OVIDED 02 DATE	03 AGENCY
01 D D SPILLED MATERIAL REMOVED 04 DESCRIPTION N/A	02 DATE	
01 D E CONTAMINATED SOIL REMOVED 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 D.F. WASTE REPACKAGED 04 DESCRIPTION N/A	-	03 AGENCY
01 D.G. WASTE DISPOSED ELSEWHERE 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 D H. ON SITE BURIAL 04 DESCRIPTION N/A	O2 DATE	03 AGENCY
01 D L IN SITU CHEMICAL TREATMENT 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 D.J. IN SITU BIOLOGICAL TREATMENT 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 D K. IN SITU PHYSICAL TREATMENT 04 DESCRIPTION N/A	Q2 DATE	03 AGENCY
01 D.L. ENCAPSULATION O4 DESCRIPTION N/A	O2 DATE	03 AGENCY
01 C M. EMERGENCY WASTE TREATMENT 04 DESCRIPTION N/A	O2 DATE	03 AGENCY
O1 C N. CUTOFF WALLS O4 DESCRIPTION N/A	O2 DATE	03 AGENCY
01 () O. EMERGENCY DIKING/SURFACE W. O4 DESCRIPTION N/A	ATER DIVERSION 02 DATE	03 AGENCY
01 D.P. CUTOFF TRENCHES/SUMP 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 D Q SUBSURFACE CUTOFF WALL 04 DESCRIPTION N/A	02 DATE	03 AGENCY

\$EPA	POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 10 - PAST RESPONSE ACTIVITIES	L IDENTIFICATION OI STATE OF SITE NUMBER MN D00617184
# PAST RESPONSE ACTIVITIES COM		
01 D R. BARRIER WALLS CONSTRUCTED 04 DESCRIPTION N/A	₩ DATE	03 AGENCY
01 D S. CAPPING/COVERING 04 DESCRIPTION N/A		03 AGENCY
01 D T. BULK TANKAGE REPARED 04 DESCRIPTION NA	© DATE	03 AGENCY
01 D U. GROUT CURTAIN CONSTRUCTED 04 DESCRIPTION N/A	© DATE	03 AGENCY
01 D V. BOTTOM SEALED NA	©2 DATE	03 AGENCY
01 D W. GAS CONTROL 04 DESCRIPTION N/A	© DATE	03 AGENCY
01 D X FIRE CONTROL O4 DESCRIPTION N/A	- 02 DATE	03 AGENCY
01 D Y. LEACHATE TREATMENT 04 DESCRIPTION N/A	62 DATE	03 AGENCY
01 D Z AREA EVACUATED NA DESCRIPTION NA	© DATE	03 AGENCY
01 D 1. ACCESS TO SITE RESTRICTED 04 DESCRIPTION N/A	C2 DATE	03 AGENCY
01 D 2. POPULATION RELOCATED 04 DESCRIPTION N/A	02 DATE	03 AGENCY
01 [] 3. OTHER REMEDIAL ACTIVITIES 04 DESCRIPTION	02 DATE	03 AGENCY

M. SOURCES OF INFORMATION (On specific information of , soon flor, compo analysis, reports

N/A

ECOLOGY AND ENVIRONMENT FILES, REGION I.



. . .

POTENTIAL HAZARDOUS WASTE SITE SITE INSPECTION REPORT PART 11 - ENFORCEMENT INFORMATION

L IDENTIFICATION

OI STATE OF SITE NAMES

MN D006171847

IL ENFORCEMENT INFORMATION

OI PAST REGULATORY/ENFORCEMENT ACTION II YES INO

02 DESCRIPTION OF FEDERAL STATE, LOCAL REGULATORY/ENFORCEMENT ACTION

N/A

ML SOURCES OF INFORMATION (CO LOCAL INFORMACIOL O. B. MADE BIOL, MARINE O'NOTHER IMPORTAL INFORMACION OF THE CONTRACT OF THE C

ECOLOGY AND ENVIRONMENT FILES, REGION I.

C

APPENDIX C

FIT SITE PHOTOGRAPHS

SITE NAME: T. O. PLASTICS

PAGE | OF 16

U.S. EPA ID: MND 006171847

TDD: F05-8811-003

PAN: FMN01885A



DATE: 6-20-89 TIME: 1450 DIRECTION OF PHOTOGRAPH: EAST PHOTOGRAPHED BY: D. SULLIVAN

WEATHER CONDITIONS: SUNNY, WINDY, 80'S SAMPLE ID (if applicable): N/A

DESCRIPTION: PERSPECTIVE OF THE PLANT 105 BUILDING. NOTE THE PROPANE TANK TO

THE LEFT.

SITE NAME: T. O. PLASTICS

PAGE 2 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ1885A

DATE: 6-20-89


TIME: 1045

DIRECTION OF PHOTOGRAPH: SW

WEATHER CONDITIONS: SUNNY WINDY 80°s

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID (if applicable): M/A



PLANT 105 DESCRIPTION: WAREHOUSES AND SILOS OF

DATE: 6-20-89

TIME: 1045


DIRECTION OF PHOTOGRAPH: SW

WEATHER CONDITIONS: SUNNY, WINDY

80°s

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID (if applicable): N/A



DESCRIPTION: WAREHOUSED AND SILOS OF 105. PLAM

SITE NAME: T.O. PLASTICS

PAGE 3 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ188SA

DATE: 6-20-89

TIME: 1245

DIRECTION OF PHOTOGRAPH:

NW

WEATHER
CONDITIONS:
SUNNY WIN

SUNNY WINDY

80'3

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



DESCRIPTION: VACUUM PUMP DISCHARGE WATER AS IT FLOWS FROM

A FIPE OUTSIDE THE PLANT 105 BUILDING. NOTE DITCH FORMED BY THE DISCHARGE WATER.

DATE: 6-20-89

TIME: 1230

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY WINDY

80 3

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID
(if applicable):



DESCRIPTION: PERSPECTIVE SHOWING PONDED WATER, WAREHOUSES,

PUMP HOUSE AND COOLING POND.

SITE NAME: T. O. PLASTICS

PAGE 4 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMN@188SA

DATE: 6-20-89

TIME: 1435

DIRECTION OF PHOTOGRAPH:
SOUTH

CONDITIONS:
SUNNY WINDY
80°5

PHOTOGRAPHED BY:
D. SULLIVAN

SAMPLE ID (if applicable):



DESCRIPTION: PERSPECTIVE OF BEAD PLANT. BUILDING LEFT OF THE

BEAD FLANT IS A COMMUNITY CENTER. CLEARWATER WATER TOWER LOCATED IN BACKGROUND.

DATE: 6-20-89

TIME: 1440

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY WINDY

80°s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): N/A



DESCRIPTION: PERSPECTIVE OF BEAD PLANT.

SITE NAME: T.O. PLASTICS

PAGE 5 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ188SA

DATE: 6-20-89

TIME: 1440

DIRECTION OF PHOTOGRAPH:

CONDITIONS:
SUNNY WINDY
80°'s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): N/A



DESCRIPTION: PERSPECTIVE OF COOLING POND. PLANT 105 FACILITY

IN THE BACKGROUND.

DATE: 6-20-89

TIME: 1445

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY, WINDY

80°s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): N/A



DESCRIPTION: PERSPECTIVE OF COOLING POND AND PLANT 105

WAREHOUSES.

SITE NAME: T.O. PLASTICS

PAGE 6 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMN@1885A

DATE: 6-20-89

TIME: 1250

DIRECTION OF PHOTOGRAPH: WEST

VEATHER
CONDITIONS:
SUNNY WINDY
80°5

PHOTOGRAPHED BY:
D. SULLIVAN

SAMPLE ID
(if applicable):
P/A



DESCRIPTION: PERSPECTIVE OF THE GRINDING AREA WITHIN THE

PLANT 105 BUILDING.

DATE: 6-20-89

TIME: 1455

DIRECTION OF PHOTOGRAPH: W5W

WEATHER
CONDITIONS:
SUNNY, WINDY

80°s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



BUILDING EXTRUSION AREA LOCATED IN THE PORTION OF THE BUILDING LEFT OF THE PLATFORM.

SITE NAME: T. O. PLASTICS

PAGE 7 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ188SA

DATE: 6-20-89

TIME: 1435

DIRECTION OF PHOTOGRAPH: WMM

WEATHER CONDITIONS: SUNNY WINDY 80's

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID (if applicable):



DESCRIPTION: PERSPECTIVE SHOWING WAREHOUSE

DATE: 6-20-89

TIME: 1430

DIRECTION OF PHOTOGRAPH: WEST

WEATHER CONDITIONS: SUNNY WINDY

80's

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID (if applicable): NIA



DESCRIPTION: PERSPECTIVE OF WAREHOUSE

SHOWING BARRELS

WHICH ALLEGEDLY CONTAIN "CUT-BACK" ASPHALT.

T.O. PLASTICS SITE NAME:

PAGE 8 OF /c

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ188SA

DATE: 6-20-89

TIME: 1430

DIRECTION OF PHOTOGRAPH:

ESE

WEATHER CONDITIONS:

SUNNY WINDY

80°'s

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID (if applicable): N/A



DESCRIPTION: PERSPECTIVE OF T.O. PLASTICS PROPERTY EAST OF SITE BUILDINGS. NOTE HOMES IN BACKGROUND AND PROPANE TANK TO THE RIGHT.

SITE NAME: T.O. PLASTICS

PAGE 9 111 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNQ SASA

DATE: 6-20-89

TIME: 1215

DIRECTION OF PHOTOGRAPH:

CONDITIONS:
SUNNY WINDY

PHOTOGRAPHED BY:

SAMPLE ID
(if applicable):
Sl



DESCRIPTION: CLOSE - UP OF SURFACE SOIL SAMPLE SI.

DATE: 6-20-89

TIME: 1215

DIRECTION OF PHOTOGRAPH:
NORTH

WEATHER
CONDITIONS:
SUNNY, WINDY

80'3

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



DESCRIPTION: PERSPECTIVE OF SURFACE SOIL SAMPLE SI COLLECTED

NEAR A LOADING PLATFORM OUTSIDE THE GRINDING AREA OF PLANT 105.

SITE NAME: T.O. PLASTICS

PAGE 10 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNO 1885A

DATE: 6-20-89


TIME: 1230

DIRECTION OF PHOTOGRAPH:
NNE

CONDITIONS:
SUNNY WINDY
80°3

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): 52



DESCRIPTION: CLOSE- UP OF SURFACE SOIL SAMPLE SZ

DATE: 6-20-89

TIME: 1230

DIRECTION OF PHOTOGRAPH:

CONDITIONS: SUNNY WINDY

80's

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): 52



DESCRIPTION: PERSPECTIVE OF SURFACE SOIL SAMPLE 52, COLLECTED

FROM A LOW LYING AREA OF PONDED WATER.

SITE NAME: T.O. PLASTICS

PAGE 11 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ1885A

DATE: 6-20-89

TIME: 1240

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY WINDY

80°3

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$3



DESCRIPTION: CLOSE - UP OF SURFACE SOIL SAMPLE S3.

DATE: 6-20-89

TIME: 1240

DIRECTION OF PHOTOGRAPH:

VEATHER
CONDITIONS:
SUNNY, WINDY

80°s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): 53



DESCRIPTION: PERSPECTIVE OF SURFACE SOIL SAMPLE S3, COLLECTED OUTSIDE OF THE BEAD PLANT.

SITE NAME: T. O. PLASTICS

PAGE 12 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ1885A

DATE: 6-20-89

TIME: |310

DIRECTION OF PHOTOGRAPH:

CONDITIONS:
SUNNY WINDY
80°5

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): S4



DESCRIPTION: CLOSE UP OF SURFACE SOIL SAMPLE S4.

DATE: 6-20-89

TIME: 1310

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY WINDY

80°s

PHOTOGRAPHED BY: D. SULLIVAN

SAMPLE ID
(if applicable):



DESCRIPTION: PERSPECTIVE OF SURFACE SOIL SAMPLE S4 COLLECTED

NEAR THE WATER DISCHARGE POINT FROM THE PLANT 105 BUILDING.

SITE NAME: T. O. PLASTICS

PAGE 13 111 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMN@1985A

DATE: 6-20-89

TIME: 1315

DIRECTION OF PHOTOGRAPH:

CONDITIONS:
SUNNY WINDY

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$5



DESCRIPTION: CLOSE-UP OF SURFACE SOIL SAMPLE S5

DATE: 6-20-89

TIME: 1315

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY, WINDY

80°s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): \$5



DESCRIPTION: PERSPECTIVE OF SURFACE SOIL SAMPLE S5, COLLECTED NEAR

THE FIRST WAREHOUSE EAST OF THE SILOS. AMONG THE BARRELS INSIDE
THE WAREHOUSE ARE THOSE LABELLED PERCHLOROETHYLENE AND ETHYLENE GLYCOL.

SITE NAME: T. O. PLASTICS

PAGE 14 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ1885A

DATE: 6-20-89

TIME: 1335

DIRECTION OF PHOTOGRAPH: SOUTH

CONDITIONS:
SUNNY WINDY

80°'s

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): 56



DESCRIPTION: CLOSE-UP OF SURFACE SOIL SAMPLE S6 COLLECTED AS

A POTENTIAL BACKGROUND SOIL SAMPLE.

DATE: 6-20-89

TIME: 1335

DIRECTION OF PHOTOGRAPH: WEST

WEATHER
CONDITIONS:
SUNNY, WINDY

80'5

PHOTOGRAPHED BY:

SAMPLE ID (if applicable):



FROM TREES EAST OF THE T.O. PLASTICS FACILITY.

SITE NAME: T.O. PLASTICS

PAGE 15 OF 16

U.S. EPA ID: MND006171847 TDD: F05-8811-003

PAN: FMNØ188SA

DATE: 6-20-89

TIME: 1355

DIRECTION OF PHOTOGRAPH:

WEATHER
CONDITIONS:
SUNNY WINDY

80°5

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): RW2



WELL AT THE T.O. PLASTICS BEAD PLANT ON-SITE.

DATE: 6-20-89

TIME: 1355


DIRECTION OF PHOTOGRAPH:

WEATHER CONDITIONS: SUNNY, WINDY

80'5

PHOTOGRAPHED BY:

SAMPLE ID (if applicable): Rw2



DESCRIPTION: PERSPECTIVE OF DRINKING WATER SAMPLE RWZ.

	FIELD F	PHOTOGRAPHY LO	G SHEET		
SITE NAME: T.O. PL	ASTIC	5		PAGE 16 OF	16
U.S. EPA ID: MND0061		DD: F05-881	1-003	PAN: FMNOI	885A
DATE: 6.20-89 NON-R	ESPONSIVE				
TIME: 1100					
DIRECTION OF PHOTOGRAPH: SSE					
WEATHER CONDITIONS: SUNNY WINDY					
80°s					
PHOTOGRAPHED BY: D. SULLIVAN					
SAMPLE ID (if applicable): RWI					
DESCRIPTION: CLOSE -	UP OF S	SAMPLE RI	NI COL	LECTED FROM	
THE CLEARWATE	R MN	MUNICIPA	AL WELL		
DATE: 6-20-89 TIME: 1100 DIRECTION OF PHOTOGRAPH: WEST	RESPONSIVE				
WEATHER CONDITIONS: SUNNY WINDY					
80°s					
PHOTOGRAPHED BY: D. SULLIVAN					
SAMPLE ID (if applicable): RWI					
DESCRIPTION: PERSPEC	TIVE OF	MUNICIPAL	WELL SA	MPLE RWI.	

APPENDIX D

U.S. EPA TARGET COMPOUND LIST AND

TARGET ANALYTE LIST

QUANTITATION/DETECTION LIMITS

ADDENDUM A

ROUTINE ANALYTICAL SERVICES

CONTRACT REQUIRED DETECTION AND QUANTITATION LIMITS

Contract Laboratory Program Target Compound List Quantitation Limits

COMPOUND	CAS #	VATER	SOIL SEDIMENT SLUDGE
	7/ 07 2	10 (1	10 "
Chloromethane	74-87-3	10 ug/L	10 ug/Kg
Bromomethane	74-83-9	10	10
Vinyl chloride	75-01-4	10	10
Chloroethane	75-00-3	10	10
Methylene chloride	75-09-2	5	5
Acetone	67-64-1	10	5 5 5 5 5
Carbon disulfide	75-15-0	5	5
1,1-dichloroethene	75-35-4	5	5
1,1-dichloroethane	75-34-3	5	5
1,2-dichloroethene (total)	540-59-0	5	5
Chloroform	67-66-3	5	5
1,2-dichloroethane	107-06-2	5	5
2-butanone (MEK)	78-93-3	10	10 -
1,1,1-trichloroethane	71-55-6	S	5
Carbon tetrachloride	56-23-5	5	5
Vinyl acetate	108-05-4	10	10
Bromodichloromethane	75-27-4	5	5
1,2-dichloropropane	78-87-5	5 5 5 5 5 5	5 '
cis-1,3-dichloropropene	10061-01-5	5	5 5 5 5 5
Trichloroethene	79-01-6	5	5
Dibromochloromethane	124-48-1	5	5
1,1,2-trichloroethane	79-00-5	5	5
Benzene	71-43-2	5	5
Trans-1,3-dichloropropene	10061-02-6		
Bromoform	75-25-2	5	5
4-Methyl-2-pentanone	108-10-1	10	10
2-Hexanone	591-78-6	10	10
Tetrachloroethene	127-18-4	5	5
Tolene	108-88-3	5	5
1,1,2,2-tetrachloroethane	79-34-5	5	5
Chlorobenzene	108-90-7	5	5
Ethyl benzene	100-41-4	5 5 5 5 5	5
Styrene	100-42-5	5	5 5 5 5 5
Xylenes (total)	1330-20-7	5	5

Table A
Contract Laboratory Program
Target Compound List
Semivolatiles Quantitation Limits

			SOIL
COMPORTE	CAC #	UATED	SEDIMENT
COMPOUND	CAS #	VATER	SLUDGE
Phenol	108-95-2	10 ug/L	330 ug/Kg
bis(2-Chloroethyl) ether	111-44-4	10	330
2-Chlorophenol	95-57-8	10	330
1,3-Dichlorobenzene	541-73-1	10	330
1,4-Dichlorobenzene	106-46-7	10	330
Benzyl Alcohol	100-51-6	10	330
1,2-Dichlorobenzene	95-50-1	10	330
2-Methylphenol	95-48-7	10	330
bis(2-Chloroisopropyl) ether	108-60-1	10	330
4-Methylphenol	106-44-5	10	330
N-Nitroso-di-n-dipropylamine		10	330
Bexachloroethane	67-72-1	10	330
Nitrobenzene	98-95-3	10	330
Isophorone	78-59-1	10	330
2-Nitrophenol	88-75-5	10	330
2,4-Dimethylphenol	105-67-9	10	330
Benzoic Acid	65-85-0	50	1600
bis(2-Chloroethoxy) methane	111-91-1	10	330
2,4-Dichlorophenol	120-83-2	10	330
1,2,4-Trichlorobenzene	120-82-1	10	330
Naphthalene	91-20-3	10	330
4-Chloroaniline	106-47-8	10	330
Hexachlorobutadiene	87-68-3	10	300
4-Chloro-3-methylphenol	59-50-7	. 10	330
2-Methylnaphthalene	91-57-6	10	330
Hexachlorocyclopentadiene	77-47-4	10	330
2,4,6-Trichlorophenol	88-06-2	10	330
2,4,5-Trichlorophenol	95-95-4	50	1600
2-Chloronaphthalene	91-58-7	10	330
2-Nitroaniline	88-74-4	50	1600
Dimethylphthalate	131-11-3	10	330
Acenaphthylene	208-96-8	10	330
2,6-Dinitrotoluene	606-20-2	10	330
3-Nitroaniline	99-09-2	50	1600
Acenaphthene	83-32-9	10	330
2,4-Dinitrophenol	51-28-5	50	1600
4-Nitrophenol	100-02-7	50	1600
Dibenzofuran	132-64-9	10	330
2,4-Dinitrotoluene	121-14-2	10	330
Diethylphthalate	84-66-2	10	330 ⁻
4-Chlorophenyl-phenyl ether	7005-72-3	10	330

Table A
Contract Laboratory Program
Target Compound List
Semivolatiles Quantitation Limits

			SOIL SLUDGE
COMPOUND	CAS #	VATER	SEDIMENT
Fluorene	86-73-7	10 ug/L	330 ug/Kg
4-Nitroaniline	100-01-6	50	1600
4,6-Dinitro-2-methylphenol	534-52-1	50	1600
N-nitrosodiphenylamine	86-30-6	10	330
4-Bromophenyl-phenylether	101-55-3	10	330
Hexachlorobenzene	118-74-1	10	330
Pentachlorophenol	87-86-5	50	1600
Phenanthrene	85-01-8	10	330
Anthracene	120-12-7	10	330
Di-n-butylphthalate	84-74-2	10	330-
Fluoranthene	206-44-0	10	330
Pyrene	129-00-0	10	330
Butylbenzylphthalate	85-68-7	10	330
3,3'-Dichlorobenzidine	91-94-1	20	660
Benzo(a)anthracene	56-55-3	10	330
Chrysene	218-01-9	10	330
bis(2-Ethylhexyl)phthalate	117-81-7	10	330
Di-n-octylphthalate	117-84-0	10	330
Benzo(b)fluoranthene	205-99-2	10	330
Benzo(k)fluoranthene	207-08-9	10	330
Benzo(a)pyrene	50-32-8	10	330
Indeno(1,2,3-cd)pyrene	193-39-5	10	330
Dibenz(a,h)anthracene	53-70-3	10	330
Benzo(g,h,i)perylene	191-24-2	10	330
,			

Table A
Contract Laboratory Program
Target Compound List
Pesticide and PCB Quantitation Limits

COMPOUND	CAS #	WATER	SOIL SEDIMENT SLUDGE
alpha-BHC	319-84-6	0.05 ug/L	8 ug/Kg
beta-BHC	319-85-7	0.05	8 ag /1 .g
delta-BHC	319-86-8	0.05	8
gamma-BHC (Lindane)	58-89-9	0.05	8
Heptachlor	76-44-8	0.05	8
Aldrin	309-00-2	0.05	8
Heptachlor epoxide	1024-57-3	0.05	8
Endosulfan I	959-98-8	0.05	8
Dieldrin	60-57-1	0.10	16
4,4'-DDE	72-55-9	0.10	16
Endrin	72-20-8	0.10	16
Endosulfan II	33213-65-9	0.10	16
4,4'-DDD	72-54-8	0.10	16 .
Endosulfan sulfate	1031-07-8	0.10	16
4,4'-DDT	50-29-3	0.10	16
Methoxychlor (Mariate)	72-43-5	0.5	80
Endrin ketone	53494-70-5	0.10	16
alpha-Chlordane	5103-71-9	0.5	80 .
gamma-chlordane	5103-74-2	0.5	80
Toxaphene	8001-35-2	1.0	160
AROCLOR-1016	12674-11-2	0.5	80
AROCLOR-1221	11104-28-2	0.5	80
AROCLOR-1232	11141-16-5	0.5	80
AROČLOR-1242	53469-21-9	0.5	80
AROCLOR-1248	12672-29-6	0.5	80
AROCLOR-1254	11097-69-1	1.0	160
AROCLOR-1260	11096-82-5	1.0	160

Table A (Cont.)

CONTRACT LABORATORY PROGRAM TARGET ANALYTE LIST (TAL) INORGANIC DETECTION LIMITS

		Dete	ction Limits
Compound	Procedure	Water (µg/L)	Soil Sediment Sludge (mg/kg)
aluminum	ICP	200	40
antimony	furnace	60	2.4
arsenic	furnace	10	2
barium	ICP	200	40
beryllium	ICP	5	1
cadmium	ICP	5	1
calcium	ICP	5,000	1,000
chromium	ICP	10	2
cobalt	ICP	50	10
copper	ICP	25	5
iron	ICP	100	20
lead	furnace	5	1
magnesium	ICP	5,000	1,000
manganese	ICP	15	3
mercury	cold vapor	0.2	0.008
nickel	ICP	40	8
potassium	ICP	5,000	1,000
selenium	furnace	5	1
silver	ICP	10	2
sodium	ICP	5,000	1,000
thallium	furnace	10	. 2
tin	ICP	40	8
vanadium	ICP	50	10
zinc	ICP	20	4
cyanide	color	10	2

ADDENDUM B

CENTRAL REGIONAL LABORATORY DETECTION LIMITS

TABLE B
CENTRAL REGIONAL LABORATORY
VOLATILE DETECTION LIMITS

PARAMETER	CAS #	DETECTION LIMIT IN REAGENT VATER
Benzene	71-43-2	1.5 ug/L
Bromodichloromethane	75-27-4	1.5
Bromoform	75-25-2	1.5
Bromomethane	74-83-9	10
Carbon tetrachloride	56-23-5	1.5
Chlorobenzene	108-90-7	1.5
Chloroethane	75-00-3	1.5
2-Chloroethyl vinyl ether	110-75-8	1.5
Chloroform	67-66-3	1.5
Chloromethane	74-87-3	10
Dibromochloromethane	124-48-1	1.5
1,1-dichloroethane	75-34-3	1.5
1,2-dichloroethane	107-06-2	1.5
1,1-dichloroethene	75-35-4	1.5
Total-1,2-dichloroethene	540-59-0	1.5
1,2-dichloropropane	78-87-5	1.5
cis-1,3-dichlopropropene	10061-01-5	2
trans-1,3-dichloropropene	10061-02-6	1
Ethyl benzene	100-41-4	1.5
Methylene chloride*	75-09-2	1
1,1,2,2-tetrachloroethane	79-34-5	1.5
Tetrachloroethene	127-18-4	1.5
Toluene*	108-88-3	1.5
1,1,1-trichloroethane	71-55-6	1.5
1,1,2-trichloroethane	79 -0 0-5	1.5
Trichloroethene	79-01-6	1.5
Vinyl chloride	75-01-4	10
Acrolein	107-02-8	100
Acetone*	67-64-1	75
Acrylonitrile	107-13-1	50
Carbon disulfide	75-15-0	3
2-butanone	78 -93 -3	(50)
Vinyl acetate	108-05-4	15
4-Methyl-2-Pentanone	108-10-1	(3)
2-Hexanone	519-78-6	(50)
Styrene	100-42-5	1
m-xylene	108-38-3	2
o-xylene**	95-47-6	
p-xylene**	106-42-3	2.5**
Total Xylene	1330-02-7	
₹		

Common Laboratory Solvents.

Blank Limit is 5X Method Detection Limit.

^() Values in parentheses are estimates.

Actual values are being determined at this time.

^{**} The o-xylene and p-xylene are reported as a total of the two.

TABLE B (cont.)
CRL
SEMIVOLATILE DETECTION LIMITS

PARAMETER	CAS #	DETECTION LIMIT	BLANK LIMIT
Aniline	62-53-3	1.5 ug/L	3 ug/L
Bis(2-chloroethyl)ether	111-44-4	1.5	3
Phenol	108-95-2	2	4
2-Chlorophenol .	95-57-8	2	4
1,3-Dichlorobenzene	541-73-1	2	4
1,4-Dichlorobenzene	106-46-7	2	4
1,2-Dichlorobenzene	95-50-1	2.5	5
Benzyl alcohol	100-51-6	2	4
Bis(2-chloroisopropyl) ether	39638-32-9	2.5	5
2-Methylphenol	95-48-7	1	2
Hexachloroethane	67-72-1	2	4
N-nitrosodipropylamine	621-64-7	1.5	4 3 5 2 -
Nitrobenzene	98-95-3	2.5	5
4-Methylphenol	106-44-5	1	2 -
Isophorone	78-59-1	2.5	5
2-Nitrophenol	88-75-5	2	4
2,4-Dimethylphenol	105-67-9	2	4
Bis(2-chloroethoxy)methane	111-91-1	2.5	5
2,4-Dichlorophenol	120-83-2	2	5 4
1,2,4-Trichlorobenzene	120-82-1	2	4 4 4
Naphthalene	91-20-3	2	4
4-Chloroaniline	106-47-8	2	4
Hexachlorobutadiene	87-68-3	2.5	5
Benzoic acid	65-85-0	(30)	(60)
2-Met hy lnapthalene	91-57-6	2	4
4-Chloro-3-methylphenol	59-50-7	1.5	3
Hexachlorocyclopentadiene	77-47-4	2	4
2,4,6-Trichlorophenol	88-06-2	1.5	3
2,4,5-Trichlorophenol	95-95-4	1.5	3
2-Chloronapthalene	91-58-7	1.5	3 3 3 3 2
Acenapthylene	208-96-8	1.5	3
Dimethyl phthalate	131-11-3	1.5	3
2,6-Dinitrotoluene	606-20-2	1	2
Acenaphthene	83-32-9	1.5	3
3-Nitroaniline	99-09-2	2.5	3 5 2
Dibenzofuran	132-64-9	1	2
2,4-Dinitrophenol	51-28-5	(15)	(30)
2,4-Dimitrotoluene	121-14-2	1	2
cont.			(**

TABLE B (Cont.)
CRL
SEMIVOLATILE DETECTION LIMITS

y•	**	÷	*
8		DETECTION	BLANK (a)
PARAMETER	CAS #	LIHIT	LIMIT
Fluorene	86-73-7	1 ug/L	2 ug/L
4-Nitrophenol	100-02-7	1.5	3 -
4-Chlorophenyl phenyl ether	7005-72-3	1	2 2
Diethylphthalate	84-66-2	1	2
4,6-dinitro-2-methylphenol	534-52-1	(15)	(30)
1,2-Diphenylhydrazine	122-66-7	1	2
n-Nitrosodiphenylamine *	86-30-6		
Diphenylamine *	122-39-4	1.5	3
4-Nitroaniline	100-01-6	3	
4-Bromophenyl-phenylether	101-55-3	1.5	6 3 3 4 2 5 - 4 3 3
Hexachlorobenzene	118-74-1	1.5	3
Pentachlorophenol	87-86-5	2	4
Phenanthrene	85-01-8	1	2
Anthracene	120-12-7	2.5	5
Di-n-butylphthalate	84-74-2	2	- 4
Fluoranthene	206-44-0	1.5	3
Pyrene	129-00-0	1.5	3
Butylbenzylphthalate	85-68-7	3.5	7
Chrysene **	218-01-9		
Benzo(a)anthracene **	56-55-3	1.5	. 3
bis(2-Ethylhexyl)phthalate	117-81-7	1	3 2 3
Di-n-octyl phthalate	117-84-0	1.5	3
Benzo(b)fluoranthene ***	205-99-2		
Benzo(k)fluoranthene ***	207-08-9	1.5	3
Benzo(a)pyrene	50-32-8	2	4
Indeno(1,2,3-cd)pyrene	193-39-5	3.5	3 4 7
Dibenzo(a,h)anthracene	53-70-3	2.5	5
Benzo(g,h,i)perylene	191-24-2	4	5 8 2
2-Nitroaniline	88-74-4	1	2

^{*} These two parameters are reported as a total.

Note: Limits are for reagent water.

^{**} These two parameters are reported as a total.

^{***} These two parameters are reported as a total.

⁽a) If the blank limit is exceeded, the sample is reextracted and rerun.

^() Values in parentheses are estimates.

The actual values are being determined at this time.

TABLE B (Cont.)
CRL
PESTICIDE AND PCB DETECTION LIMITS

		DETECTION	
PARAMETER	CAS #	LIMIT	
Aldrin	309-00-2	0.005 ug/L	
alpha BHC	319-84-6	(0.010)	
beta BHC	319-85-7	(0.005)	
delta BHC	319-86-8	(0.005)	
gama BHC (Lindane)	58-89-9	0.005	
Chlordane	57-74-8	(0.020)	
4,4'-DDD	72-54-8	(0.020)	
4,4'-DDE	72-55-9	(0.005)	
4,4'-DDT	50-29-3	0.020	
Dieldrin	60-57-1	0.010	
Endosulfan I	959-98-8	0.010	
Endosulfan II	33213-65-9	0.010	
Endosulfan sulfate	1031-07-8	(0.10)	
Endrin	72-20-8	0.010	
Endrin aldehyde	7421-93-4	(0.030)	
Endrin ketone	53494-70-5	(0.030)	
Heptachlor	76-44-8	0.030	
Heptachlor epoxide	1024-57-3	0.005	
4,4'-Methoxychlor	72-43-5	0.020	
Toxaphene	8001-35-2	(0.25)	
PCB-1242	53469-21-9	(0.10)	
PCB-1248	12672-29-6	(0.10)	
PCB-1254	11097-69-1	(0.10)	
PCB-1260	11096-82-5	(0.10)	

^() Values in parentheses are estimates.
Actual values are being determined at this time.

Note: Limits are for reagent water.

TABLE B (Cont.)
CRL
INORGANIC DETECTION LIMITS

					:
	PB 0 0 D D D D	DETECTION		D.1110D	
COMPOUND	PROCEDURE	LIHITS		RANGE	UNITS
Aluminum	ICP	100	. 80	to 1,000,000	ug/L
Antimony	Furnace	2		to 30	ug/L
Arsenic	Furnace	2	2	to 30	ug/L
Barium	ICP	50	6	to 20,000	ug/L
Beryllium	, ICP	5		to 20,000	ug/L
Boron	ICP	80	80	to 20,000	ug/L
Cadmium	ICP	10	10	to 20,000	ug/L
Cadmium	Furnace	0.2		to 2	ug/L
calcium	ICP	1000	0.5	to 1,000	mg/L
Chromium	ICP	10	8	to 20,000	ug/L
Cobalt	ICP	10	6	to 20,000	ug/L
Copper	ICP	10		to 20,000	ug/L
iron	ICP	100		to 1,000,000	ug/L
Lead	Furnace	2		to 30	ug/L
Lead	ICP	70	70	to 20,000 -	ug/L
Lithium	ICP	10		to 20,000	ug/L
Magnesium	ICP	1000	0.1	to 200	mg/L
Maganese	ICP	10	5	to 20,000	ug/L
Mercury	Cold vapor	0.2	0.1	to 2	ug/L
Holybdenum	ICP	15	15	to 20,000	ug/L
Nickel	ICP	20	15	to 20,000	ug/L
Potassium	ICP	2000	5	to 1,000	mg/L
Selenium	Furnace	2	2	to 30	ug/L
Silver	ICP	5	6	to 10,000	ug/L
Sodium	ICP	1000	1	to 1,000	mg/L
Strontium	ICP	10	10	to 20,000	ug/L
Sulfide	Titration	1	<	1	mg/L
Sulfide	Color	0.05	<	1	mg/L
Thallium	Furnace	2	2	to 30	ug/L
Titanium	ICP	25	25	TO 20,000	UG/L
Tin	ICP	40		to 20,000	ug/L
Vanadium	ICP	10	5	to 20,000	ug/L
Yttrium	ICP	5		to 20,000	ug/L
Zinc	ICP	20	40	to 1,000,000	ug/L
Cyanide	AA	5.0	8	to 200	ug/L

Note: The above list may or may not contain compounds that are routinely analyzed at CRL for low level detection limits for drinking water.

See inorganic Routine Analytical Services for related CAS #.

ADDENDUM C

SPECIAL ANALYTICAL SERVICES DETECTION LIMITS

Drinking Water Samples

TABLE C SPECIAL ANALYTICAL SERVICES DRINKING WATER VOLATILE QUANTITATION LIMITS

PARAMETER	CAS #	DETECTION LIHIT IN REAGENT VATER
Benzene	71-43-2	1.5 ug/L
Bromodichloromethane	75-27-4	1.5
Bromoform	75-25-2	1.5
Bromomethane	74-83-9	1.5
Carbon tetrachloride	56-23-5	1.5
Chlorobenzene	108-90-7	1.5
Chloroethane	75-00-3	1.5
2-Chloroethyl vinyl ether	110-75-8	1.5
Chloroform	67-66-3	1.5
Chloromethane	74-87-3	1.5
Dibromochloromethane	124-48-1	1.5
1,1-Dichloroethane	75-34-3	1.5
1,2-Dichloroethane	107-06-2	1.5
1,1-Dichloroethene	75-35-4	1.5
Total-1,2-Dichloroethene	540-59-0	1.5
1,2-Dichloropropane	78-87-5	1.5
cis-1,3-Dichloropropene	10061-01-5	2
trans-1,3-Dichlopropropene	10061-02-6	1
Ethyl benzene	100-41-4	1.5
Methylene chloride *	75-09-2	1
1,1,2,2-Tetrachloroethane	79-34-5	1.5
Tetrachloroethene	127-18-4	1.5
Toluene *	108-88-3	1.5
1,1,1-Trichloroethane	71-55-6	1.5
1,1,2-Trichloroethane	79-00-5	1.5
Trichloroethene	79-01-6	1.5
Vinyl chloride	75-01-4	1.5
Acrolein	107-02-8	25
Acetone *	67-64-1	5
Acrylonitrile	107-13-1	25
Carbon disulfide	75-15-0	3
2-Butanone	78-93-3	5
Vinyl acetate	108-05-4	5
A-Methyl-2-pentanone	108-10-1	1.5
2-Hexanone	519-78-6	5
Styrene	100-42-5	1
Xylene (total)	1330-02-7	1.5

^{*} Common laboratory solvents.
Blank limit is 5x method detection limit.

^() Values in parentheses are estimates. actual values are being determined at this time.

TABLE C (cont.) SAS DRINKING WATER SEHIVOLATILES QUANTITATION LIMITS

	~.~ "	DETECTION	
PARAMETER	CAS #	LIHIT	
Aniline	62-53-3	1.5 ug/l	
Bis(2-chloroethyl)ether	111-44-4	1.5	
Phenol	108-95-2	2	
2-Chlorophenol	95-57-8	2	
1,3-Dichlorobenzene	541-73-1	2	
1,4-Dichlorobenzene	106-46-7	2	
1,2-Dichlorobenzene	95-50-1	2.5	
Benzyl alcohol	100-51-6	2	
Bis(2-chloroisopropyl)ether	39638-32-9	2.5	
2-Methylphenol	95-48-7	1	
Hexachloroethane	67-72-1	2	
n-Nitrosodipropylamine	621-64-7	1.5	
Nitrobenzene	98-95-3	2.5	
4-Methylphenol	106-44-5	1	
Isophorone	78-59-1	2.5	
2-Nitrophenol	88-75-5	2	
2,4-Dimethylphenol	105-67-9	2	
Bis(2-Chloroethoxy)methane	111-91-1	2.5	
2,4-Dichlorophenol	120-83-2	2 .	
1,2,4-Trichlorobenzene	120-82-1	2	
Naphthalene	91-20-3	2	
4-Chloroaniline	106-47-8	2	
Hexachlorobutadiene	87-68-3	2.5	
Benzoic Acid	65-85-0	20	
2-Methylnapthalene	91-57-6	2	
4-Chloro-3-methylphenol	59-50-7	1.5	
Hexachlorocyclopentadiene	77-47-4	2	
2,4,6-Trichlorophenol	88-06-2	1.5	
2,4,5-Trichlorophenol	95-95-4	1.5	
2-Chloronapthalene	91-58-7	1.5	
Acenapthylhene	208-96-8	1.5	
Dimethyl phthalate	131-11-3	1.5	
2,6-Dinitrotoluene	606-20-2	1	
Acenaphthene	83-32-9	1.5	
3-Nitroaniline	99-09-2	2.5	
Dibenzofuran	132-64-9	1	
2,4-Dinitrophenol	51-28-5	(15)	
2,4-Dinitrotoluene	121-14-2	i	

TABLE C (Cont.) SAS DRINKING WATER SEMIVOLATILE QUANTITATION LIMITS

		DETECTION	
PARAMETER	CAS #	LINIT	
Fluorene	86-73-7	1 ug/L	
4-Nitrophenol	100-02-7	1.5	
4-Chlorophenyl phenyl ether	7005-72-3	1	
Diethyl phthalate.	84-66-2	î	
4,6-Dinitro-2-methylphenol	534-52-1	(15)	
1,2-Diphenylhydrazine	122-66-7	1	
n-Nitrosodiphenylamine *	86-30-6	_	
Diphenylamine *	122-39-4	1.5	
4-Nitroaniline	100-01-6	3	
4-Bromophenyl-phenylether	101-55-3	1.5	
Hexachlorobenzene	118-74-1	1.5	
Pentachlorophenol	87-86-5	2	
Phenanthrene	85-01-8	1	
Anthracene	120-12-7	2.5	
di-n-Butyl phthalate	84-74-2	2	
Fluoranthene	206-44-0	1.5	
Pyrene	129-00-0	1.5	
Butyl benzyl phthalate	85-68-7	3.5	
Chrysene **	218-01-9	•	
Benzo(A)Anthracene **	56-55-3	1.5	
bis(2-ethylhexyl)phthalate	117-81-7	1	
di-n-Octyl phthalate	117-84-0	1.5	
Benzo(b)fluoranthene ***	205-99-2		
Benzo(k)fluoranthene ***	207-08-9	1.5	
Benzo(a)pyrene	50-32-8	2	
Indeno(1,2,3-cd)pyrene	193-39-5	3.5	
Dibenzo(a,h)anthracene	53-70-3	2.5	
Benzo(g,h,i)perylene	191-24-2	4	
2-Nitroaniline	88-74-4	1	

^{*} These two parameters are reported as a total.

Note: Limits are for reagent water.

^{**} These two parameters are reported as a total.

^{***} These two parameters are reported as a total.

^() Values in parentheses are estimates.
The actual values are being determined at this time.

TABLE C (Cont.) SAS DRINKING WATER PESTICIDE AND PCB QUANTITATION LIMITS

	DETECTION	
CAS #	LIHIT	
300 00 2	0.005.44/1	
	•	
·		
	•	
-		
	-	
11097-69-1	0.10	
11096-82-5	0.10	
	309-00-2 319-84-6 319-85-7 319-86-8 58-89-9 5103-71-9 5103-74-2 72-54-8 72-55-9 50-29-3 60-57-1 959-98-8 33213-65-9 1031-07-8 72-20-8 7421-93-4 53494-70-5 76-44-8 1024-57-3 72-43-5 8001-35-2 12674-11-2 11104-28-2 11141-16-5 53469-21-9 12672-29-6 11097-69-1	309-00-2

^() Values in parentheses are estimates.
Actual values are being determined at this time.

Note: Limits are for reagent vater.

TABLE C (Cont.) SAS DRINKING WATER INORGANIC DETECTION LIMITS

		D D D D D D D D D D D D D D D D D D D	
D 4 D 4 4 4 D T D D	BD A GBDIMD	DETECTION	
PARAMETER	PROCEDURE	LIMIT	
Aluminum	ICP	100	
Antimony	GFAA	5	
Arsenic	GFAA	5	
Barium	ICP	50	
Beryllium	. ICP	5	
Cadmium	GFAA	0.5	
Calcium	ICP	1000	
Chromium	ICP	10	
Cobalt	ICP	10	
Copper	ICP	10	
Iron	ICP	100	
Lead	GFAA	2	
Magnesium	ICP	1000	
Manganese	ICP	10	
Mercury	Cold Vapor	0.2	
Nickel	ICP .	20	
Potassium	ICP	2000	
Selenium	GFAA	. 2	
Silver	1CP	5	
Sodium	ICP	1000	
Thallium	GFAA	2	
Tin	ICP	40	
Vanadium	ICP	10	
Zinc	ICP	20	
Cyanide	Colorimetric	10	
-			

Note: The above list may or may not contain compounds that are routinely analyzed at CRL for low level detection limits for drinking water.

See inorganic Routine Analytical Services (RAS) for related CAS #.

,

WATER WELL RECORD DEPARTMENT OF HEALTH 123153 for Water Sample Minnesota Statutes 1664.01-.08 3. PROPERTY OWNER'S PANE WELL LOG 2 w exact location of well in section gri NON-RESPONSIVE LL DEPTH (completed) Date of Completion 81 n. 10-14-75 Cable tool 4 Reverse 10 Dug 7 Dri ven Eollow rod ALF OF € Bored 110_ I ROLLTY 6 Jetted Power Auger . USE Domestic Public Supply Industry 2 Irrigation Air Conditioning 8 Commercial HARDIESS OF COLOR PROM PORMATION LOG Test Well **6**D____ . CASING HEIGHT: Above/Below Black So Et. Med 2 Threaded 21 Velded 3 Black 2 GALT. D Hond 72 in. to 8/ ft. depth mol in. to____ ft. depth Hord _in. to___ ____ft. depth | Drive Shoe! Yes # No____ 8. SCREEN Or open bole from ft. to --__ Dis._ Set between ____ ft. and ____ ft. ____ ft. and ____ ____ ft. and ____ ft. 9. STATIC WATER LEVEL 5C ft. below above Date Measured 10 11-75 10. PUMPING LEVEL (below land surface) 50 rt. arter / hrs. pumping ____ft. after_____hrs. pumping 11. VELL KEAD COMPLETION To Pitless adapter To Basement offset To At least 12" above grade 12. Well grouted? Yes Bo Cu. Yds.___ 1 | Seat cement 2 | Bentonite Depth: from ____ft. to___ from ____ft. to 13. Searest source of possible contamination _____feet _____direction Well disinfected upon completion? Yes. [No] Date installed 1- 17 7 LOCATED BY Hot installed 1 - Address Verification HICKOTOR 2 · Name on Mailbox Hodel Number 1/4/1/2 P Volta 2 3 13 Length of drop pipe 6 2 ft. capacity 12

Material of drop pipe 1" A 1-14 D 12 fg 3 - Let Block Plat Book 5 - Ki Inlo. From Owner 3 t.S. Turbine Type: [Submersible S Reciprocating 6 - Info. From Neighbor 2 Jet 4 Centri fugal 7 · □ Other_ ☐ Can't Loca'e State Why This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Use a second sheet, if needed. REMARKS, ELEVATION, SOURCE OF DATA, etc. A-QWTA Authorised Representative MININ GEOLOGICAL SUBVEY CODY

MINNESOTA UNIQUE WELL NO.

STATE OF MINNESPITA

Q.,	NON-	والمستعدد المنطوعة			g Gaprater 134	
	DECROMONIE :	NON-	NON-	٦٠	• •	NON- WELL LOG 3 7
-	Outpace and Objection from Road Intersections or Street Ad	House and City of West Locali		354		RESPONSIV
	Show exact incution of well an account and with "L."	NO.	N-RESPO	Melve		a. WELL DEFTH (completed) Date of Completion
	NON-RESPONSIVE	****	N-RESPU	NOIVE		85° 6" well . 10-19-78
						Color soil 4 Revent 10 hours 16 Dec
		back Promby				20 Notice and 40 Au 40 brees 110
		Les Promier				A USE
						Promotic 4 Police Supply 10 malesty
-		COLOR	HARDNESS OF	FROM	TO	3 Horigations S Manacopal S Commenced
•	Top Soil	Black		0	2	7. CASING HEIGHT: Above/Bdow HOLE DEAN
					54.70	2: Cut standard Surface 48m n.
	Sand	Brown		2	44	Drine Shoet Yes No
	Sandy Clay	Brown		44	60	in, to
		7 - 10 - 10 - 10 - 10 - 10 - 10 - 10 - 1				I SURELLA TO COORD NOW
	Sandy Clay	Grey		60	85	Make from 11. to &
•						Plastic ou C
						Set browse 55 n. mc 85 n.
	NON-RESPONSI	VE				nn
						9. STATIC WATER LEVEL
						43 nitter Oser Oser 10-19-78
		 	1	- 0		10. PUMPING LEVEL (below tond surface) 60 b. efter 1 br. componer 20
						t. other he, pompeng
5	NON-RESPONSIVE					II. WELL HEAD COMPLETION
						(□ Proces adapter 2□ basenest offset Æ At least 1:" shreeg grade 12. Well grouted?
						□va 8 %
			30			1 Prices Comen 2 Dentourie 3
						Dryth from ft. to ft.
						13 heartst sources of possible contamination
i						Hert disinfected apos completion: Vesil In-
		71.000				14. PUMP
	LOCATE	DIDY	╅			Out meaned 10-24-78
	4					Manufactured hance Webtrol
- 1 - 1	2 - 1 Name on	errication -				Model heather
	3 · D Lot-Block		-			Length of drop page 1 n. casectry Material of drop page 1 galvinised
	4 · Pat Book					Type: (@Submanuble ADL-8. Turbine s©Recurrenting
8	5 - 🔲 Into. From					2 16. WATER WELL CONTRACTOR'S CEPTIFICATION
	6 ☐ Info. From 7 - ☐ Other	Reighbor				This well was drilled under my parisdiction and this report is true to
		e State Why	=			the test of my knowledge and belief.
	Caream	one seer. If seeded	-			Front Vella, Inc. 73457
·	A REMARKS STAVATION SOURCE OF DATA OF					Rt. 4, St. Cloud, MI 56301
Ī	A-QW	74				
•	A-QW					Authorized Representative
	Lege	and the second				GART 10-19-78
	MINN. GEOL	OGICAL SURV	EY COPY			- 5/74 30M - 7/76 30M

NON-				a Barum 154	4.01.00 C 1955
NON- NON	- NON- N	C I tac	:NO	N- SPON	NON-RESPONSIVE LOG
NON-	Address and City of Well Location			- 10	
ON-RESPONSIVE		ON-	h map of we	li location.	4. WELL DEPTH (completed) Dete of Completion
ON REOF ONOTVE	Addition Name	IUN- PESPONS			564-1977
					5. C'sNe tool 4 Revene 7 Driven 10 Dag
	Black Number				3 Hollow rod SD As & Street 110
<u></u>	Los Number				Minter) 6 letted 9 Prover Auger 6. USE
					■ Domestic 4□Public Supply 7□ Industry
<u> </u>		The bond of or			2 Irrigation S Municipal B Commerce
	COTOR	HARINLSS OF FORMATION	FROM	10	1 1 1 1 1 1 1 1 1 1
Send	Drown	moft		16	I Back Threaded
					3□G ₆ h. s□Welded Surfaceft.
Sand Pine	Brown		16	25	Drive Shoe 1 Ves 5. No
Clay	Gray		35	42	in. toin. toin. to
		1			in. to ft. Weight lbs./ft in. to
Sand	Gray		42	67	S. SCREEN Or open hole from ft. to n.
Clay	Gray		67	30	Type stainless steel Du. A"
CIAG	Utay		0/	70	Sot/Gause Length FITTINGS:
	į.				Sei between
					n. and n.
NON PER	PONSIVE				. STATIC WATER LEVEL
NON-RES	PUNSIVE				27 Pall Indian above Date Messured 17
S					10. PUMPING LEVEL (below land surface)
					ft. after brs. pumping t.p.s
					11. WELL HEAD COMPLETION
			F-10-20		Priless adapter 2 Basement offset 3 At least 12" above grade
			1		12. Well pouted?
					□ Yes
					Depth: fromft. toft.
	i.				from ft. to ft.
					13. Nearest sources of possible contamenation Transfer Level direction Septic ty
					See
	LOCATED BY				I4. PUMP
	Address Verification				Date installed 9-9-77
T 17750	Vaire on Mailbox				Not installed
	ot-B'ock	9			Manufacture* Name Model Number & D. 12x SO HP & Voits 250
	at Book				Length of drop pipe 28 ft. capacity 12 sec
, —	nio. From Owner			1	Material of drop pipe 1" galuani med steel
	nto Frem Neight	dr		1	Type: Submersible SULS. Terbbis SUReciprocaling
	Othe				2 Jet 4 Centriligat 6 16. WATER WELL CONTRACTOR'S CERTIFICATION
	Can' Locate State	Why			This well was drilled under my jurisdiction and this report is true to
				1	the best of my knowledge and ballef.
2000					Trant Mile Inc. 73157 License Business Name License No.
Use to REMARKS, ELEVATION, SOURCE OF DATA.	second sheet, if needed.				Address Rt 64 St. Clouds. Ms. 56301
b 6)	WTA			ex.	Address 1
IT - W	V- , , ,				Signed At Tay Company 7-7-7
					influoridad Reprofuntative
					TO THE TAX
				-	Mame of Driller

NON-		TOE E	MATE	MELL!	uscone - John Jahnhus
NON- NON-	Name House	Section No. Proc	Para Para Para Para Para Para Para Para	M EMM 17	1. PROPERTY OWNER'S HAME
NON-	NON-	NO	1	* *	NON-RESPONSIVE
NON-RESPONSIVE		<u> </u>			Address
Hen near enterne					
ON-RESPONSIVE	N	ION-	map of m	d location.	4. WELL DEPTH (completed) Date of Completion
	Addition Pears	ESPONSI	/		94' 3/22/78
					5. 1 Calle tool 4 Review 10 hours 16 Day.
	Block Number			-	20 Hollow red SCAr SC Bored 110
					3 Motory Colored Corone Agent
-	Let Number				6. USE
					Chomatic 4 Parks Supply 1 Indian
		THE POWER OF			2⊡trrigation €Disamcepal BD(Sama
	COLOR	HARITHESS OF FORMATION	FROM	то	3 ☐ Test Well 6 ☐ Air Conditioning 6 ☐ 7. CASING HEJIGHT. Abors/Below HOLE D
Topeoil	Slock	Soft	0'	3.	Induck de Threshol
	1	1	<u> </u>	† •	2 Gan sounded Senter L'Abores.
Sand	Brown	Soft	1.	62'	10 45 Drive Short Ya X No
	- BYAR		•	-	4 10 94 A Wages 21 NAME. 4-104
Sond	Grey	Hard	42'	90'	a. ways a.,m. b. so_
Genral & Water	_		90'	96	Nate Charge St. to
*	į				Type Steinless Steel De 4"
					Southern 10 Learn 41
NON-RESPONSI	VE			8	Set between _90 R. and _94 R.
				2	
					1. STATIC WATER LEVEL
				8.0	
		V	E.	-	10. PUMPING LEVEL (below land surface)
					n. etter ten. pumping 18 : s
					11. WELL HEAD COMPLETION
<u> </u>		-			The Process adapter 2. Suscenses of the distribution of the last 12" phone grade
	10				12. Well prouted?
		-			□ Ya X № Cs. Yé
				İ	1 Nest Central 2 Best conte 3
-		-		-	Depts: from ft. to ft.
380 T	İ		1	1	from ft. to ft.
			1	1	13. Nearest sources of potable continuation
					West disorfected upon completons* 1 de No.
1 10	DEATED BY	11			14. PUMP
1 - □ Add	ress Verification			0.000000	Date baselied _6/27/78
2 - 🔲 Na-	re on Mailbex	100	144		☐ Not that affect
	Biock-		1-		Manufacture's Name Gould
4 - Flat	Book		1		Model Number 10E 105412 Hr 1 voto 230
5 - 11 Inio	From Owner	+	-		Length of drop plot 63 N. capacity 8
100 P	. From Neighte	x	1		teatered of drop paper Type: g□Surinscrubble S□L.S. Turbure S□Hecoprocating
7 - 1 015		$\pm \pm \pm$			Type: 4 Schmernide 3 L.S. Tarbor S Hecoprocating
	't Locate State	Why			16. WATER WELL CONTRACTOR'S CERTIFICATION
					This well was drilled seater day persidence and this report is true to
	4	1			the best of my knowledge and belief.
					Donahauer Well & Pump Co. 73061
	second sheet, if arrest		1		
REMARKS ELEVATION, SOURCE OF DATA OR	1.00m				Route 2 St. Joseph, Ma. 5637
A-QU) TH				27.1 57.7
11 0000					Signed Approximate Representation Date
			···		Quentia Donobouer Date 3/72
		~ ~~~	-		\$174.3

ON-RESPONSIVE					1.01.0H Jor Water Somphi
					NON-RESPONSIVE
					Address
					WELL LOG 6
NON-RESPONSIVE	detion Name	2.	ich map of w	d location.	4. WELL DEFTH (completed) 94 n. 4-26-83
					\$ 100 Sectors 40 Revenue 10 Detrois 10 Dag
tot.	ick Number				2 Hottow rid SDAir #DBored 110
· · · · · · · · · · · · · · · · · · ·	or Number				3□ History 6□ Jetted 9□ Prover Auger
	of Number				a. USE
		HARIIMESS OF	T		2 treignition 5 Manuscipus SC commercial
2. FORMATION LOG	(010#	HARIMESS OF	FROM	10	3 Test Well 6 An Cradditioning 90 7. CASING MEIGHT Above/Show MOLE DIAM
CLAY SAND	Beaux	M	0	56	10 Cart. Stated Surface 2 8.
SAND ROCKS	a navel	M	54	60	
	BROLON		200	_	10 = 10 73 n. wager 10 = 94 cc
FINE, COMESE, SAN	BROWN	M	600	70	
COARSE SAND, GR	BROWN	H	70	70	SCREEN OHNSON Or open hole from n. ton.
CURRES TRUJER	- Sicour	M	10	2	Tron SE, On 10" teles,
FINC SAND	GREY	1/_	TP.	28	Son / Gause 40 -10-35 Longit 20' 10"
COMPSE GRAVER	6000	M	88	94	Set between 73 ft. and 94 ft.
10 4021 FG SV	Cay	11	011	11	• STATIC WATER LEVEL
MARL	GREEN	17	74		56 ft British Dahoue Date Measured 9-7-95
			İ		10. PUMPING LEVEL (below land surface) (3) (1, after 2 br. pumping 230 pp.
77.5					ft. after hes. pumping g p.m.
,			-		11. WELL HEAD COMPLETION MON TER
					2 Basemeni offset Mari Frant 12' above grade
			1		LE WELL OROUTED?
	 	17 18 5		-	I Neal Cement 2 Benkente 30
×					Growt material from to ft .Cu Yes
	ļ		-		13. NEAREST SOURCES OF POSSIBLE CONTAMINATION
					—————————————————————————————————————
		-			14. PUMP
			 		Date installed Not installed
					Date installed Not installed
*					Model Number HP Volta
	1	2000 2000	-	- XX 10 - XX 1	Length of drop pipe ft. capacity
0.00-0.00.00 to 0.00-0.00		ā.			Material of drop pape Type: submicrathle
					2
Use a second 15 REMARKS, ELEVATION, SOURCE OF DATA, sec.	nd sheet, if needed				16. WATER WELL CONTRACTOR'S CERTIFICATION This well was drilled under my jurisdiction and this report is tree to
and the second s					the best of my knowledge and builef."
₽≦ ⁸⁹		B			FISCHER Well Co. 73/35
866					Box 1101 St Clous
2002	æ				
± 4 0 ⊛					Signed Keith Deviabal Date 8-9-83 Authorized Representative DAN DONABAUST Date 8-9-83 Name of Deliver
		2			DAN DONABAUST 8-9-83
IMPORTA	NT:	0	100	794	Neme of Dritter 5/74 30M 7/78 30M 7/78 30M
FILE WITH DEED - WE	IL OWNER CO	PY .	LAU	134	1/78 30W 2/10 10M

APPENDIX E

WELL LOGS OF THE AREA OF THE SITE

w exact location of well in section grid ON-RESPONSIVE	with "X."	Sketch pup NON- RESPON	of well	location.	70 Date of Completion 5/29/1976
		SIVE			Cable tool 4 Reverse 7 Driven 10 Dug 2 Bollow rod 3 Air 6 Bored 11
PORMATION LOG	COLOR	HARDWESS OF PORMATION	PRON	70	Domestic
Sand	Brown	med	0	57	7. CASIBG BEIGHT: Above/Below DIAM.
Water Sand	Brown	med	57	70	Threaded 1 Velded 2 Surface f:
					in, to
					6. SCREEN Or open hole from r. to r.
NON BESD	MCIVE				Dia. Dia.
NON-RESPO	INSIVE				Set between ft. and ft.
					ft. and ft.
					9. STATIC VAIER LEVEL 53 ft. below above Date Measures 5/29/76 10. Publish Level (below land surface)
					53 r. after hrs. pumping 12 g.p.m
		-			ft. after hrs. pumping g.p.m. 11. WELL MEAD COMPLETION
				-	1 Pitless adapter 2 Basement offset 2 At least 12" above grade
, NON-RESPO	ONSIVE				Yes No Cu. Yds
				1)	1 Sest cement 2 Sentonite 3
\	, , ,			 	froeft. toft.
	LOCATED BY				13. Hearest source of possible contamination feet
1 · □ A	dress Verification	on		-	Well disinfected upon completion? Temas No
	ame on Mailbox			_	Dom Date installed 6/1/76
	ot-Block				Manufacturer's Name ACTINICOF
	at Book fo. From Owner				Model Fumber SD 12x 50 EF1/2 Volta 230
	to. From Neight		-	-	length of drop pipe 53 ft. capacity g.p.a
,	ther				Naterial of drop pipe 1" galvanised
	an'i Locate Stat	Why			
			1	-	16. WATER WELL CONTRACTOR'S CERTIFICATION
					This well was drilled under my jurisdiction and this report is true to
					the best of my knowledge and belief.
Dee a a	second sheet, if needed.			1	Traut Wel 1 Drilling 73157
A -QL					Address 18 Lincoln Ave. N.E. St Cloud Signed Authorized Representative

in-RESPONSIVE					J. PROPERTY OWNER'S NAME		
ance and Durctions from Road Interiorities or Bry	of Address and City of Pull Location	NON- RESPONSIVE					
NON-RESPONSIVE		Batch	and and	ler etere	4 WELL DEFTH (completed) Door of Completent		
NON-IXESPONSIVE	Addition Rome	N-RESPÖ	NSIVE				
					Cable tool Cereme 10 Drives 10 Day		
	Block Number				20 Holom red 50 Ar 60 Breed 110		
					ADMINISTRATION ADDRESS AND A STREET AND A ST		
	Lot Number				a USE		
	1				Phomesics 4 Public Supply 10 Industry		
L					3 Stringstone S Nanocopal S A Communi		
FORMATION LOG	COTON	HARIMESS OF	FROM	10	3 Test hell 6 As Conditioning		
					1. CASING HEICHT: Above/Below HOLE DLAN		
Top Soil	Black		0	2	(Thresded		
					2 Cosh stated Burtoce 881 N.		
Sand	Brown		2	44	Drive Shoe! Yes No		
Sandy Clay	Brown		44	60	N. 50 N. Weidy Bull		
	an ven	1		-	for. to ft. Weight Sha_ft to		
Contra Man	Const	1 1	60	85	4. SCREEN Or open hole		
Sandy Clay	Grey		80	97	Make ft.16 ft.		
					Tre Plastic Du C		
					StockGoesse 40 Longth 20		
					Set between 55 R. and 85 n.		
					0.00		
NON		^					
NON-	NO				1. STATIC WATER LEVEL		
. 35520	NSI						
	I COA	1		7	land surface		
	NON-RES	PONSIVE			10. PUMPING LEVEL (haters land surface)		
NON RESPONSIVE					ft. after her. pumping		
NON-RESPONSIVE					11. WELL HEAD COMPLETION		
					1 Profess adapter 2 Bosement offset At least 1; shrine grade		
					12. Well grosted?		
					Dra IN CLYA		
		7:			1 hest Cemess 2 bestoate 1		
					from		
		1			13 hearest sources of possible consuments or		
					100 feet 200 derection tree		
		1			14. PUMP		
	700	-	-		Dute sentalled		
LOCA	TED BY	1			Waldwa?		
1 · [] Address	Vertication -	1					
2 · Name					Model humber Hi 3/4 Lacs 230		
		-	-		Length of drop pape 529 R. capacity		
3 - Lot-Biox	2-77				Material of drop page 1 th galvinized		
4 - Pat Bo					Type (Subscribble ADL & Technic SC Recognicating		
5 - Into. Fr	om Owner				2□Jet 4□Centrifugal 4□		
	om Neighbor				14. WATER WELL CONTRACTOR'S CERTIFICATION		
7 - Other	1.77				The well was drilled under my jurisdiction and this report in true to		
		-			the best of my knowledge and bullet.		
Can't L	oca e State Why				Trant Wells, Inc. 73457		
(e a second mer. If needed	1			Laconare Business Name Laconare has		
REMARKS, ELEVATION, SOURCE OF BATA	ek.				Men Bt. 4, St. Cloud, ME 55301		
A h	ALTA				Address to the State of the Sta		
P1-W 1	11 14						
1					Signed Ascharized Representative		
A-Q1							
			-		GART 0-19-		
					hame of Dellar		

ION-RESPONSIVE

ION-RESPONSIVE

SN-IKESI SNSIVE					A PROPERTY OWNER'S NAME
					Ma Ba Manaha Cata was
					Address
					Q
					4. WELL DEFTH (completed) Date of Completion
NON-RESPONSIVE	Addition Name	N-		111111111111111111111111111111111111111	491 0000 NOSCHOOL 0000 0000 0000 0000 0000 0000 0000
	RE	SPONSI\	/ E		94" . 3/22/78
			,		* 10 th tot 40 trust 10 trees 140 big.
	Block Hemher				3 11-8-re red 5 As 8 5 borrd 11 -
					3 Noters 6 Sented 9 Prover Apper
	Lat Number				€ USL
					Thomastic Suppry 7 Industry
					2⊡tragation s⊃Moncopal s⊃Communcal
PORMATION LOG	COLOR	HARTHHESS OF FORMATION	FROM	10	3. Test Well 6. Air Conditioning 6.
• •	Dr. A	0.0	-		1. CASING NEXCHT. Above/Below HOLE DIAM 18 Disch districteded
Topsoil	Black	Soft	0.	8.	VI AL
Sand	Brown	Soft	180	62'	JO Diffe Short Yes X. No
			1		4 = 10 94 n. wort 11 n.m. 4 = 10 94"
Sond	Gray	Hard	42'	90'	to to th. Wright the_/ft th. to ft.
Granel & Weter			90'	94	L SCREEN Or open hole from
			1	-	G 11 G 1
NON-RESPO	NSIVE				FITTINGS.
					Set berness _90_ R. and _94_ R.
				-	
					t.mlt
					9. STATIC WATER LIVEL
					56 Date Order Date Date Housered 3/22/78
					10. PUNPING LEVEL (helow land surface)
		1			-56 n. ofter -1 bes presping -18 -10-
		-	-	-	fi. sher br. punpungg.s.t.
		1 .	1	1	11. WELL HEAD COMPLETION
		-	1-	-	9 Pedess adapter 2 theremost officer of A1 least 12 always grade
	1		1		12. Well provide?
		-	-	-	□ Vo X № Cx.Ya
			1	1	1 Hest Censel 3 Bestonce 3
		-		-	Depts: from
		1	1	1	hos n. to n.
		-	-	-	23. Hoserest acorces of gooseble contamunation
			1		feetfype
	LOCATED BY		-	-	Well deserved upon completeen* 14 No.
1	Carried and Artifaction of the Control of the Contr	1 1	1	1	14 MIMP
	Address Verification		-		Date Installed _6/27/78
2.	Name on Mailbex				☐ Not installed
13 🗇	Let Block	+	-	-	Manufacturer's Name Gould
	Fiat Book				Model Number 10E 105412 Hr 1 vots 230
	Into. From Owner		-	1	Longits of drop page 63 N. Capacity 8 Lam.
			1	1	Material of drop page Type: q[]Submersible NULS. Turbus \$ Recupercating
	Into. From Neighter				Type: all:Sounceside XDL.S.Turbuse SDRecuprocating
	Other		1	1	2□ Act 4□ Centrelaga 6□
	Can't Locate State	Why			14. WATER WELL CONTRACTOR'S CERTIFICATION
					This well was drilled under my jurisdiction and this report is true to
					the best of my knowledge and bullef.
					Donabaser Well & Pump Co. 73061
	Lier a second short. If needed.				Lecuser Bullium Name Lecuser No.
IS. REMARKS. ELEVATION, SOURCE OF DE	ATAL ME.				Route 2 St. Joseph, Mn. 56374
0	11172				
A-Q	011				Signed Ascharland Resources (Prince)
					Authorized Representative
					Quantin Donohouse 3/22/70
					Quentia Donabouer Der. 3/22/78
*******		יי רחחי			\$714.30%